

**Amendment to UK submission for amendments to Regulations No.109 Retread Commercial Vehicle Tyres – Document TRANS/WP.29/GRRF/2002/19**

Further to discussions with ETRTO the UK wishes to propose the following amendments to document TRANS/WP.29/GRRF/2002/19. The changes are made apparent by “strikethrough” and italic font.

Paragraph 2.21.2 – Amend to read:

2.21.2 the nominal ----- Regulation, *or, depending on the tyre design type, the nominal outer diameter expressed in mm ;*

Insert a new paragraph 2.21.4 to read:

2.21.4 *an indication of the tyre to rim fitment configuration when it differs from the standard configuration and is not already expressed by the symbol “d” denoting the nominal rim diameter code.*

Insert a new paragraph 3.2.12 to read:

3.2.12 ~~An identification of the tyre to rim fitment configuration, when it differs from the standard configuration.~~ In the case of tyres first approved after [1 January 2009] the identification referred to in *paragraph 2.21. 4* shall be placed only immediately after the rim diameter marking referred to in paragraph 2.21.3 of this Regulation.

Annex 3 –amend to read:

2. In the particular case of tyres having a tyre to rim fitment configuration “A”, the marking shall be in the form of the following example:

~~————— 185-560 R 400A ——— where:~~  
~~————— 185 is the nominal section width in mm~~  
~~————— 560 is the outer diameter expressed in mm~~  
~~————— R is an indication of the structure of the tyre – see paragraph 3.1.3 of this Regulation~~  
~~————— 400 is the nominal diameter of the rim expressed in mm~~  
~~————— A is the tyre to rim fitment configuration.~~

*235-700 R 450A where:*

*235 is the nominal section width in mm*

*700 is the outer diameter expressed in mm*

*R is an indication of the structure of the tyre – see paragraph 3.1.3 of this Regulation*

*450 is the nominal diameter of the rim expressed in mm*

*A is the tyre to rim fitment configuration.*

*The marking of the load index, speed category date of manufacture and other markings, shall be as given in example 1 above.*

Paragraph (a) to read:

(a) the size designation ~~-----~~ as defined in paragraph 2.21 of this Regulation shall be grouped as shown in the above ~~example~~ examples: 250/75 R 20 and 235-700 R 450A. ~~In the case where the tyre to rim fitment configuration differs from standard see paragraph 3.1.10 of this Regulation.~~

Paragraph (b) to read:

(b) the service description comprising the load index and the speed symbol shall be placed immediately after the tyre size designation as defined in paragraph 2.21 of this Regulation; and following the identification of the tyre to rim fitment configuration where applicable (see paragraph 3.1.10 of this Regulation);