

Revised proposal to document TRANS/WP.29/GRE/2003/8

PROPOSAL FOR DRAFT AMENDMENTS TO REGULATION No. 7

(Position, stop, and end-outline marker lamps)

Transmitted by the expert from the Working Party "Brussels 1952" (GTB)

Note: The text reproduced below was prepared by the expert from GTB in order to insert into Regulation No. 7 provisions regarding distributed lighting systems. The suggested amendments to the Regulation are marked in **bold** characters. When preparing the proposal the following documents have been taken into account:

- The GTB proposal to include in Regulation No. 48 provisions regarding distributed lighting systems as well as all definitions relating to light sources (TRANS/WP.29/GRE/2001/31/Rev.1);
- The GTB proposal to include in Regulation No. 98 provisions regarding distributed lighting systems (TRANS/WP.29/GRE/2001/30); a revised version (TRANS/WP.29/GRE/2003/10) will be submitted for the fiftieth GRE session;
- The draft amendments approved by WP.29/AC.1 (Supplement 7 to the 02 series of amendments, TRANS/WP.29/2002/52) and by GRE (Supplement 8 to the 02 series of amendments, TRANS/WP.29/GRE/49, annex 3).
- **Report of the 50th session TRANS/WP.29/GRE/50**

Note: This document is distributed to the Experts on Lighting and Light-Signalling only.

A. PROPOSAL

Paragraph 1.6., replace in the text the words "filament lamp" by "**light source**".

Add new paragraph 1.7., to read:

"1.7. "lens" means the outermost component of a signal lamp unit which transmits light through the illuminating surface.

Add new paragraph 2.1.6., to read:

"2.1.6. Whether a distributed lighting system is used and which function(s) is (are) intended to be provided by this system."

Paragraph 2.2.2., amend to read:

"2.2.2. A brief technical description stating, in particular, with the exception of lamps with non-replaceable light sources:

- the category or categories of **light source prescribed; in the case of filament lamps or gas-discharge light sources, this** shall be one of those contained in Regulation No. 37 or No. 99; or
- the light source module specific identification code.

In the case of ..."

Insert new paragraphs 2.2.3. and 2.2.4., to read:

"2.2.3. A brief technical description including the make(s) and type(s) of the ballast(s) and/or the components of the distributed lighting system, where it applies.

2.2.4. If the gas-discharge light source in a distributed lighting system is not approved according to Regulation No. 99, information describing the light source sufficiently to permit identification. This information shall include a drawing with dimensions and the basic electrical and photometric values, an indication whether the light source complies with the UV radiation requirements of paragraph 3.10. of Regulation No. 99 and a test report related to paragraph 5.9. of this Regulation."

Paragraph 2.2.3. (former), renumber as paragraphs 2.2.5.

Paragraph 2.2.4. (former), renumber as paragraphs 2.2.6. and amend to read :

"2.2.6. Two samples (in the case of a distributed lighting system two complete systems); if the approval is ..."

Paragraph 2.2.5. (former), renumber as paragraph 2.2.7.

Paragraph 3.2., amend to read.

"3.2. Must bear a clearly legible and indelible marking indicating the category or categories of **light sources** prescribed; this is not valid for lamps with non-replaceable light sources;"

Paragraph 4.1.2., amend to read.

"4.1.2. When two or more lamps are part of the same unit of grouped, combined or reciprocally incorporated lamps **or of a distributed lighting system**, approval may be granted only if each of these lamps satisfies the provisions set out in this Regulation or in another Regulation. Lamps not satisfying the provisions of any of those Regulations shall not be part of such unit of grouped, combined or reciprocally incorporated lamps. This provision shall not apply to headlamps fitted with a double-filament **light source**, where only one beam is approved."

Add new paragraphs 5.7. to 5.13., to read:

"5.7. **In case of a distributed lighting system the gas-discharge light source used in the light-generator may be a non-replaceable gas-discharge light source not approved according to Regulation No. 99. In all other cases the gas-discharge light source(s) shall be replaceable and approved to Regulation No. 99.**

5.8. **In the case of replaceable gas-discharge light sources the lamp holder shall conform to the dimensional characteristics as given on the data sheet of IEC Publication 60061-2, relevant to the category of gas-discharge light source used. The gas-discharge light source shall fit easily into the lamp.**

5.9. **The interval between the time of activation of a lamp or distributed lighting system and the time the photometric and colorimetric requirements in point HV are met shall not exceed 200 ms.**

5.10. **The distributed lighting system, when equipped with (a) gas-discharge light source(s), shall not generate radiated or power line disturbance to cause malfunction of other electric/electronic systems of the vehicle. 2/**

5.11. **Light transmitting components made of plastic material shall be tested for their resistance to light source radiations:**

The following test shall be done:

Flat samples of each light transmitting plastic component of the lamp are exposed to the light of the gas-discharge light source. The parameters such as angles and distances of these samples shall be the same as in the lamp. These samples shall have the same colour and surface treatment, if any, as the parts of the lamp.

After 1,500 hours of continuous exposure, the colorimetric specifications of the transmitted light must be met with a new standard gas-discharge light source,

