

Regulation No. 52:

5.7.8.1. Each seating place shall have a vertical clearance of not less than 90 cm from the highest point of the undepressed seat cushion and at least 135 cm from the floor where the feet of the seated passenger rest. In the case of vehicles to which paragraph 5.7.1.9 applies, this dimension may be reduced to 120 cm.

Proposal:

5.7.8.1. **Over each seating position and, except in the case of the seats(s) alongside the driver, its associated foot space, there shall be measured a free space with a height** of not less than 900 mm **measured** from the highest point of the **uncompressed** seat cushion and at least 1350 mm from the **mean level of** the floor **in the foot space**. In the case of vehicles to which paragraph 5.7.1.9. applies, and **also for the seats(s) alongside the driver, these** dimensions may be reduced to 1200 mm **measured from the floor and 800 mm measured from the highest point of the uncompressed seat cushion**.

Regulation 107.02:

7.7.8.6.1. In the case of single deck vehicles, over each seating position and, except in the case of the front row seats in a vehicle not exceeding 22 passengers, its associated foot space, there shall be measured a free space with a height of not less than 900 mm measured from the highest point of the uncompressed seat cushion and at least 1350 mm from the mean level of the floor in the foot space. In the case of vehicles to which paragraph 7.7.1.10. applies, this dimension may be reduced to 1200 mm measured from the floor.  
In the case of double deck vehicles, each seating position shall have a free height of not less than 900 mm measured from the highest point of the uncompressed seat cushion. This free height shall extend over the vertical projection of the whole area of the seat and the associated foot space. In the case of the upper deck, this free height may be reduced to 850 mm."

Proposal:

7.7.8.6.1. In the case of single deck vehicles, over each seating position and, except in the case of the **seats(s) alongside the driver in a vehicle of Class A or B**, its associated foot space, there shall be measured a free space with a height of not less than 900 mm measured from the highest point of the uncompressed seat cushion and at least 1350 mm from the mean level of the floor in the foot space. In the case of vehicles to which paragraph 7.7.1.10. applies, **and also for the seats(s) alongside the driver in a vehicle of Class A or B, these dimensions** may be reduced to 1200 mm measured from the floor **and 800 mm measured from the highest point of the uncompressed seat cushion**.  
In the case of double deck vehicles, each seating position shall have a free height of not less than 900 mm measured from the highest point of the uncompressed seat cushion. This free height shall extend over the vertical projection of the whole area of the seat and the associated foot space. In the case of the upper deck, this free height may be reduced to 850 mm.