



**Economic and Social
Council**

Distr.
GENERAL

ECE/TRANS/WP.29/2009/14
17 December 2008

ENGLISH
Original: ENGLISH AND FRENCH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations

One-hundred-and-forty-seventh session
Geneva, 10 - 13 March 2009
Item 4.2.4 of the provisional agenda

1958 AGREEMENT

Consideration of draft amendments to existing Regulations

Proposal for Corrigendum 2 to Supplement 12 to the 02 series of amendments to
Regulation No. 7
(Front and rear position (side) lamps, stop lamps and end-outline marker lamps)

Submitted by the Working Party on Lighting and Light-Signalling (GRE) */

The text reproduced below was adopted by GRE at its sixtieth session. It is based on ECE/TRANS/WP.29/GRE/2008/47, not amended. It is submitted to WP.29 and AC.1 for consideration (ECE/TRANS/WP.29/GRE/60, para. 24).

*/ In accordance with the programme of work of the Inland Transport Committee for 2006-2010 (ECE/TRANS/166/Add.1, programme activity 02.4), the World Forum will develop, harmonize and update Regulations in order to enhance performance of vehicles. The present document is submitted in conformity with that mandate.

Paragraph 4.2.2.2., amend to read:

"4.2.2.2. ... (side) lamps, the letter "R" followed or not by the figure "1" when the device produces steady luminous intensity and by the figure "2" when the device produces variable luminous intensity."

Paragraph 4.2.2.4., amend to read:

"4.2.2.4. ...the letters "R" or "R1" or "R2" and "S1" or "S2" as the case ..."

Paragraph 5.7., amend to read:

"5.7. In case of failure of the variable intensity control of:
 (a) a rear position lamp category R2 emitting more than the maximum value of category R or R1;
"

Paragraph 6.1., amend the table to read:

"

<u>3/</u>	Minimum luminous intensity in cd	Maximum luminous intensity in cd when used as		
		Single lamp	Lamp (single) marked "D" paragraph (4.2.2.6.)	Total for the assembly of two or more lamps <u>4/</u>
....				
6.1.3. Rear position lamps, rear end-outline marker lamps				
6.1.3.1. R or R1 (steady)	4	12	8.5	17
6.1.3.2. R2 (variable)	4	30	21	42
6.1.4. Stop-lamps				
6.1.4.1. S1 (steady)	60	185	130	260
6.1.4.2. S2 (variable)	60	521	365	730
6.1.4.3. S3 (steady)	25	80	55	110
6.1.4.4. S4 (variable)	25	114	80	160

"
