



Economic and Social Council

Distr.: General
22 December 2011

Original: English

Economic Commission for Europe

Inland Transport Committee

World Forum for Harmonization of Vehicle Regulations

156th session

Geneva, 13–16 March 2012

Item 4.9.9 of the provisional agenda

1958 Agreement – Consideration of draft amendments to existing Regulations submitted by GRE

Proposal for Supplement 3 to the 01 series of amendments to Regulation No. 98 (Headlamps with gas-discharge light sources)

Submitted by the Working Party on Lighting and Light-Signalling *

The text reproduced below was adopted by the Working Party on Lighting and Light-Signalling (GRE) at its sixty-sixth session in order to simplify the photometric test requirements, clarify the heat test requirements, correct the test voltage requirements and correct the UV radiation requirements of LED modules and clarify that they are of the "low UV" type. It is based on ECE/TRANS/WP.29/GRE/2011/38, not amended, ECE/TRANS/WP.29/GRE/2011/39, as amended by paragraph 20 of the report (ECE/TRANS/WP.29/GRE/66, paras. 19, 20, 27 and 35), ECE/TRANS/WP.29/GRE/2011/44, not amended, and ECE/TRANS/WP.29/GRE/2011/52, not amended. It is submitted to the World Forum for Harmonization of Vehicle Regulations (WP.29) and to the Administrative Committee (AC.1) for consideration.

* In accordance with the programme of work of the Inland Transport Committee for 2010–2014 (ECE/TRANS/208, para. 106, ECE/TRANS/2010/8, programme activity 02.4), the World Forum will develop, harmonize and update Regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.

Paragraph 2.2.5.2.2., amend to read:

"2.2.5.2.2. If provisions are taken to shield the relevant headlamp components from UV radiation, e.g. by glass filters, or;"

Insert new paragraph 2.2.5.2.3., to read:

"2.2.5.2.3. If low-UV-type LED modules are being applied as specified in Annex 11 of this Regulation."

Paragraph 6.2.4.2., amend to read:

"6.2.4.2. One additional light source according to Regulation No. 37, and/or one or more LED module(s) inside the passing beam headlamp, may be used for the purposes of generating infrared radiation. It/they shall only be activated at the same time as the gas discharge light source. In the event that the gas-discharge light source fails, this additional light source and/or LED module(s) shall be automatically switched off."

Paragraphs 6.2.4.4., amend to read:

"6.2.4.4. Measurement conditions with respect to light sources

6.2.4.4.1. In the case of a gas-discharge light source:

The voltage applied to the terminals of the ballast(s) is either 13.2 V +/- 0.1 for 12 V systems or otherwise specified (See Annex 7).

6.2.4.4.2. In the case of a filament light source according to Regulation No. 37:

The lamp shall be measured by means of an uncoloured standard (étalon) filament lamp designed for a rated voltage of 12V. During the checking, the voltage at the terminals of the filament lamp shall be regulated so as to obtain the reference luminous flux at 13.2V as indicated at the relevant data sheet of Regulation No. 37.

6.2.4.4.3. In the case of LED module(s):

The lamp shall be measured at 6.3 V, 13.2 V or 28.0V respectively, if not otherwise specified within this Regulation. LED module(s) operated by an electronic light source control gear, shall be measured as specified by the applicant."

The table in Paragraph 6.2.5., delete line 1

Annex 4, paragraphs 2.2.1. to 2.2.2., amend to read:

"2.2.1. The result expressed in milliradians (mrad) shall be considered as acceptable for a passing beam headlamp when the absolute value $\Delta r_1 = | r_3 - r_{60} |$ recorded on the headlamp is not more than 1.0 mrad ($\Delta r_1 \leq 1.0$ mrad) upward and not more than 2.0 mrad ($\Delta r_1 \leq 2.0$ mrad) downwards.

2.2.2. However, if this value is:

<i>movement</i>	
upward	more than 1.0 mrad but not more than 1.5 mrad ($1.0 \text{ mrad} < \Delta r_1 \leq 1.5 \text{ mrad}$)
downward	more than 2.0 mrad but not more than 3.0 mrad ($2.0 \text{ mrad} < \Delta r_1 \leq 3.0 \text{ mrad}$)

a further sample of a headlamp shall be tested as described in paragraph 2.1. after being subjected three consecutive times to the cycle as described below, in order to stabilize the position of mechanical parts of the headlamp on a base representative of the correct installation on the vehicle:

Operation of the passing beam for one hour, (the voltage shall be adjusted as specified in paragraph 1.1.1.2.),

After this period of one hour, the headlamp type shall be considered as acceptable if the absolute value Δr measured on this sample meets the requirements in paragraph 2.2.1. above."

Annex 11, Paragraph 4.1., amend to read:

"4.1. UV-radiation

The UV-radiation of a low-UV-type LED module shall be such that: ...

This value shall be calculated using intervals of one nanometre. The UV-radiation shall be weighted according to the values as indicated in the Table UV below:

Table UV

Values according to "IRPA/INIRC Guidelines on limits of exposure to ultraviolet radiation". Wavelengths (in nanometres) chosen are representative; other values should be interpolated.

λ	$S(\lambda)$	λ	$S(\lambda)$	λ	$S(\lambda)$
250	0.430	305	0.060	355	0.000 16
255	0.520	310	0.015	360	0.000 13
260	0.650	315	0.003	365	0.000 11
265	0.810	320	0.001	370	0.000 09
270	1.000	325	0.000 50	375	0.000 077
275	0.960	330	0.000 41	380	0.000 064
280	0.880	335	0.000 34	385	0.000 053
285	0.770	340	0.000 28	390	0.000 044
290	0.640	345	0.000 24	395	0.000 036
295	0.540	350	0.000 20	400	0.000 030
300	0.300				

"