

ISO 10844:2014

Comparison to 2011 version

Douglas Moore

ISO

September 2014

Overview

- ISO 10844 republished in 2014
- Identified editorial corrections made
- No change to fundamental requirements

Clause	ISO 10844:2011	ISO 10844:2014	Effect
4.3	<p>NOTE Until more results for validation are available, <i>ENDT</i> is not part of the normative part of this International Standard. The present state of the art with respect to this method is described in Annex A but is restricted to cases where no elastic material (rubber, polyurethane, etc) is applied in the top layer or sub-layers except for modification of bitumen by less than 1 % by mass of the total mix. Polymer-modified bitumen allows higher temperature operation and reduced surface wear.</p>	<p>have no elastic material (rubber, polyurethane, etc.) applied in the top layer or sub-layers except for modification of bitumen less than 1% by weight of the total mix.</p>	<p>Brings allowance for polymer modified bitumen into main body of text</p>
4.4	<p>Subparagraph numbering continuous from 4.3 through 4.4</p>	<p>Subparagraph numbering restarted in each paragraph.</p>	<p>Improvement in clarity</p>
5.2.1	<p>refer to ISO 13473-3 and 13472-4</p>	<p>refer to ISO 13473-4</p>	<p>Corrected ISO reference in both cases</p>
5.2.2	<p>Removal of spike data is necessary. For details refer to ISO/TS 13473-6</p>	<p>Removal of spike data is necessary. Spike data shall be removed prior to further processing of the data. NOTE ISO/TS 13473-4 gives examples of spike removal processes. Spikes are data artefacts that are not part of the texture under measurement.</p>	<p>Clarification of mandatory data processing. Corrected ISO reference and inclusion of note.</p>
Annex A.8	<p>Worked out example had incorrect intermediate units (dB) and incorrect final value</p>	<p>Units and final value now correct</p>	<p>Reference example provides valid results.</p>