## UNITED NATIONS



## Economic and Social Council

Distr. GENERAL

TRANS/WP.29/625 2 June 1998

ENGLISH Original: ENGLISH and FRENCH

## ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

Working Party on the Construction of Vehicles

## CORRIGENDUM 2 TO THE 02 SERIES OF AMENDMENTS TO REGULATION No. 51

(Noise of M and N categories of vehicles)

<u>Note</u>: The text reproduced below was adopted by the Administrative Committee (AC.1) of the amended 1958 Agreement at its eighth session, following the recommendation by the Working Party at its one-hundred-and-fourteenth session. It is based on document TRANS/WP.29/1998/10, as corrected (TRANS/WP.29/609, paras. 70 and 121).

GE.98-

TRANS/WP.29/625 page 2

<u>Annex 3</u>,

<u>Paragraph 3.1.2.4.2.1.</u>, add at the end the following text (including also a new footnote 5/):

".... However, if during the test, in the case of vehicles having more than two separate gears, there is an automatic down-shift to first gear, this downshift may be avoided, at the manufacturer's choice, either by:

Increasing the speed of the vehicle  $V_A$  to a maximum of 60 km/h; or

by

Maintaining the speed  $V_{\rm\scriptscriptstyle A}$  at 50 km/h with the fuel supply to the engine limited to 95 per cent of the supply necessary for full load.  $\underline{5}/$ 

<sup>&</sup>lt;u>5</u>/ <u>Note</u>: This condition shall be considered satisfied in the case of a positive-ignition engine when the angle of opening of the throttle is 90 per cent, and, in the case of a compression-ignition engine, when the movement of the feed-rack of the injection pump is limited to 90 per cent of its stroke."