

**INFORMAL GROUP ON GASEOUS FUELLED VEHICLES
Within the UN GRPE (WP29)
PROPOSED AMENDMENT**

Name of Organisation submitting Amendment/Work Item
AEGPL

Person submitting Item
Salvatore Piccolo

Address/phone/email coordinates
AEGPL
Rue Belliard 15-17
1040 Brussels
Belgium
T: + 32 2 893 11 25
F: + 32 2 893 11 29
s.piccolo@federchimica.it

Regulation name and reference number
Proposed amendment to supplement 4 to Regulation 115 (ECE/TRANS/WP.29/2009/117).

Name of Amendment/Work Item

Proposal for an amendment to Regulation 115 introducing modifications to definition of bi-fuel vehicle and new associated requirements.

Specific language for Amendment/Work Item
English

Rationale: (Why is it important/required?)

The proposed amendments are aimed at redefining the class of bi-fuel vehicles to permit the simultaneous use of gas and petrol in gas mode.

In order to avoid overemployment of petrol, provisions are provided to limit its use in amount and duration.

These modifications are needed primarily for the approval of retrofit systems intended to be fitted on vehicles equipped with petrol direct injection systems, where, in order to safeguard the petrol injectors, a certain amount of petrol needs to be injected also in gas mode, especially when particular temperature conditions are reached.

Please submit new work items to:

Andre Rijnders, Chairman (RDW, Netherlands) rijnders@rdw.nl

Acting secretariat(s)

Jeffrey Seisler (IANGV/Clean Fuels Consulting) jseisler@cleanfuelsconsulting.org

Salvatore Piccolo (on behalf of AEGPL) s.piccolo@federchimica.it

Changes are made on bold characters and/or via strikethroughs :

Paragraphs 2.1.3., 2.1.4 and 6.1.2.2. amend to read:

- 2.1.3. "A vehicle is considered mono-fuel", when, after the retrofit operation, **it is designed primarily for permanent running on LPG or CNG, but may still have a petrol system for emergency purposes, where the capacity of the petrol tank does not exceed 15 litres.** ~~it is equipped with a petrol tank of capacity ≤ 15 litres, that can only be used to "limp home".~~
- 2.1.4. "A vehicle is considered bi-fuel" when, after the retrofit, ~~it is equipped to operate on both petrol and LPG or CNG, with a petrol tank capacity exceeding 15 litres.~~ **operation, it is equipped with a gas storage and a separate petrol storage with a capacity exceeding 15 litres, and is designed to run on only one fuel at a time. The simultaneous use of both fuels is limited in amount or duration.**
- 6.1.2.2. Fuel requirements by the engine: the type of fuel normally used by the engine could be:
(a) LPG only (**LPG mode**) in case of (mono-fuel)⁴
(b) ~~Both~~ Either unleaded petrol (**petrol mode**) or LPG (**LPG mode**) in case of (bi-fuel)
(c) Both diesel fuel or diesel fuel and LPG (dual fuel)
- (Provisions for dual fuel have still to be defined).

Par. 6.1.2.4.1.3, insert a title (new)

- 6.1.2.4.1.3. **Exhaust emissions test in petrol mode**
Subject to the requirements of paragraph 6.1.2.4.1.5., the tests shall be repeated three times using reference petrol. The parent vehicle(s), equipped with the retrofit system, shall comply with the limit values according to the type approval of the original vehicle(s) including the deterioration factors applied during the type approval of the original vehicle(s).

Par. 6.1.2.4.1.6. amend to read and insert new subparagraphs 6.1.2.4.1.6.1 and 6.1.2.4.1.6.2:

- 6.1.2.4.1.6. **Exhaust emissions test in LPG mode**
Subject to the requirements of paragraph 6.1.2.4.1.8., the tests shall be repeated three times with each reference LPG.
The parent vehicle, equipped with the retrofit system, shall comply with the limit values according to the type approval of the original vehicle(s) including the deterioration factors applied during the type approval of the original vehicle(s).

6.1.2.4.1.6.1 Engine starting-up

It is permissible that the engine is started on petrol and switched to LPG after a predetermined period of time which cannot be changed by the driver
If the parent vehicle complies with Regulation No. 83, 05 series of amendments,

or with Directive 98/69/EC, or with Regulation No. 49, 04 series of amendments, or with Directive 1999/96/EC, the ~~vehicle shall not use petrol for more than a maximum of aforesaid period of time shall not exceed~~ 90 seconds during each test.

For vehicles complying with later series of amendments to Regulations Nos. 83 and 49, or later amending Directives or European Regulations, this period shall not exceed 60 seconds.

6.1.2.4.1.6.2 Additional requirements for petrol use

It is permissible to use petrol simultaneously with gas during the entire test cycle provided that the energy consumption of gas is larger than 80% of the total amount of energy consumed during the test.

This percentage shall be calculated in accordance with the method set out in Annex 6A.

Par. 6.1.2.2., amend to read:

6.2.2.2. Fuel requirements by the engine: the type of fuel normally used by the engine could be:

- (a) CNG only (**CNG mode**) **in case of** (mono-fuel)⁴
- (b) ~~Both Either~~ unleaded petrol (**petrol mode**) or CNG (**CNG mode**) **in case of** (bi-fuel)
- (c) Both diesel fuel or diesel fuel and CNG (dual fuel)

(Provisions for dual fuel have still to be defined).

Par. 6.2.2.4.1.3, insert a title (new):

6.2.2.4.1.3. Exhaust emissions test in petrol mode

Subject to the requirements of paragraph 6.2.2.4.1.5., the tests shall be repeated three times using reference petrol. The parent vehicle(s), equipped with the retrofit system, shall comply with the limit values according to the type approval of the original vehicle(s) including the deterioration factors applied during the type approval of the original vehicle(s).

Par. 6.2.2.4.1.6. amend to read and insert new subparagraphs 6.2.2.4.1.6.1 and 6.2.2.4.1.6.2:

6.2.2.4.1.6. Exhaust emissions test in CNG mode

Subject to the requirements of paragraph 6.2.2.4.1.8., the tests shall be repeated three times with each reference CNG.

The parent vehicle(s), equipped with the retrofit system, shall comply with the limit values according to the type approval of the original vehicle(s) including the deterioration factors applied during the type approval of the original vehicle(s).

6.2.2.4.1.6.1 Engine starting-up

It is permissible that the engine is started on petrol and switched to CNG after a predetermined period of time which cannot be changed by the driver

If the parent vehicle complies with Regulation No. 83, 05 series of amendments, or with Directive 98/69/EC, or with Regulation No. 49, 04 series of amendments, or with Directive 1999/96/EC, the ~~vehicle shall not use petrol for more than a maximum of aforesaid period of time shall not exceed~~ 90 seconds during each test.

For vehicles complying with later series of amendments to Regulations Nos. 83 and 49, or later amending Directives or European Regulations, this period shall not exceed 60 seconds.

6.2.2.4.1.6.2 Additional requirements for petrol use

It is permissible to use petrol simultaneously with CNG during the entire test cycle provided that the energy consumption of gas is larger than 80% of the total amount of energy consumed during the test.

This percentage shall be calculated in accordance with the method set out in Annex 6B.

Addition of a new Annex 6A “Bi-fuel vehicle - Calculation of LPG energy consumption”:

Annex 6A

Bi-fuel vehicle - Calculation of LPG energy consumption

1. Measurement of the LPG mass consumed during the cycle

Measurement of the LPG mass consumed during the Type 1 test cycle shall be done by a fuel weighing system capable to measure the weight of the LPG storage container during the test in accordance with the following:

- (a) an accuracy of ± 2 per cent of the difference between the readings at the beginning and at the end of the test or better;**

Precautions shall be taken to avoid measurement errors.

Such precautions shall at least include the careful installation of the device according to the instrument manufacturers' recommendations and to good engineering practice

Other measurement methods are permitted if an equivalent accuracy can be demonstrated.

2. Calculation of the LPG energy ratio

The fuel consumption value shall be calculated from the emissions of hydrocarbons, carbon monoxide, and carbon dioxide determined from the measurement results assuming that only LPG is burned during the test.

The LPG ratio of the energy consumed in the cycle is then determined as follows:

$$G_{LPG} = M_{LPG} * 100 / (FC_{mean} * dist * d)$$

Where:

G_{LPG}	the LPG energy ratio
M_{LPG}	the LPG mass consumed during the cycle (kg)
FC_{mean}	the mean fuel consumption calculated in accordance with paragraph 6.1.2.4.3.2.
dist	distance travelled during the cycle (km)
d	density $d=0.538\text{kg/liter}$

Addition of a new Annex 6B “Bi-fuel vehicle - Calculation of CNG energy consumption”:

Annex 6B

Bi-fuel vehicle - Calculation of CNG energy consumption

1. Measurement of the CNG mass consumed during the cycle

Measurement of the LPG mass consumed during the Type 1 test cycle shall be done by a fuel weighing system capable to measure the weight of the CNG storage container during the test in accordance with the following:

- (a) an accuracy of ± 2 per cent of the difference between the readings at the beginning and at the end of the test or better;

Precautions shall be taken to avoid measurement errors.

Such precautions shall at least include the careful installation of the device according to the instrument manufacturers' recommendations and to good engineering practice

Other measurement methods are permitted if an equivalent accuracy can be demonstrated.

2. Calculation of the CNG energy ratio

The fuel consumption value shall be calculated from the emissions of hydrocarbons, carbon monoxide, and carbon dioxide determined from the measurement results assuming that only CNG is burned during the test.

The CNG ratio of the energy consumed in the cycle is then determined as follows:

$$G_{CNG} = M_{CNG} * 100 / (FC_{mean} * dist * d)$$

Where:

G_{CNG}	the CNG energy ratio
M_{CNG}	the CNG mass consumed during the cycle (kg)
FC_{mean}	the mean fuel consumption calculated in accordance with paragraph. 6.2.2.4.3.2
dist	distance travelled during the cycle (km)
d	density d=0.654kg/m³

“
