

**Economic and Social Council**Distr.: General
11 August 2014

Original: English

Economic Commission for Europe**Inland Transport Committee****World Forum for Harmonization of Vehicle Regulations****Working Party on Lighting and Light-Signalling****Seventy-second session**

Geneva, 20–22 October 2014

Item 4 (i) (iv) of the provisional agenda

1958 Agreement - Regulations**Other business – Any other business****Proposal for Supplement 4 to the 01 series of amendments to
Regulation No. 119 (Cornering lamps)****Submitted by the expert from the International Automotive Lighting
and Light Signalling Expert Group (GTB)***

The text reproduced below was prepared by the expert from the GTB to amend the photometric stability requirements. The modifications to the existing text of the Regulation are marked in bold for new or strikethrough for deleted characters.

* In accordance with the programme of work of the Inland Transport Committee for 2012–2016 (ECE/TRANS/224, para. 94 and ECE/TRANS/2012/12, programme activity 02.4), the World Forum will develop, harmonize and update Regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.

I. Proposal

Annex 3, paragraph 3.3., amend to read:

“3.3 For any cornering lamp except those equipped with filament lamp(s), the luminous intensities, measured after one minute and after ~~30~~ **10** minutes of operation, shall comply with the minimum and maximum requirements. The luminous intensity distributions after one **and after 10** minutes of operation ~~can~~ **shall** be calculated from the luminous intensity distribution **measured** after **photometric stability has occurred** ~~30 minutes of operation~~ by applying at each test point the ratio of luminous intensities measured at 45°L 2.5° D ~~after one minute and after 30 minutes of operation~~ for a left-side lamp (the L angle should be substituted for the R angle for a right-side lamp):

- (a) **after one minute;**
- (b) **after 10 minutes; and**
- (c) **after photometric stability has occurred.**

Photometric stability has occurred means the variation of the luminous intensity for the specified test point is less than 3 per cent within any 15 minute period.”

II. Justification

1. According to Regulation No. 119, cornering lamps that are equipped with light sources other than filament lamps, are required to meet the relevant photometric requirements after one minute and after 30 minutes of operation.

2. However, under normal traffic conditions these lamps, taking into account specification requirements of various carmakers that reflect the hardest conditions of operation, are being operated for no more than 6 minutes. Subsequently, it is proposed to carry out the second measurement after 10 minutes instead of 30 minutes. This will also harmonize the requirements with standard SAE J1889.¹

¹ <http://standards.sae.org/>