



Economic and Social Council

Distr.: General
26 December 2014

Original: English

Economic Commission for Europe

Inland Transport Committee

World Forum for Harmonization of Vehicle Regulations

165th session

Geneva, 10-13 March 2015

Item 4.9.3 of the provisional agenda

**1958 Agreement – Consideration of draft amendments
to existing Regulations submitted by GRE**

Proposal for Supplement 8 to the 04 series of amendments to Regulation No. 19 (Front fog lamps)

Submitted by the Working Party on Lighting and Light-Signalling*

The text reproduced below was adopted by the Working Party on Lighting and Light-Signalling (GRE) at its seventy-second session (ECE/TRANS/WP.29/GRE/72, para. 39). It is based on ECE/TRANS/WP.29/GRE/2014/18, not amended. It is submitted to the World Forum for Harmonization of Vehicle Regulations (WP.29) and to the Administrative Committee AC.1 for consideration.

* In accordance with the programme of work of the Inland Transport Committee for 2012–2016 (ECE/TRANS/224, para. 94 and ECE/TRANS/2012/12, programme activity 02.4), the World Forum will develop, harmonize and update Regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.

Insert a new paragraph 3.5.3., to read:

"3.5.3. If the LED module(s) are non-replaceable, the markings for LED module(s) are not required."

Annex 1, item 10.3., amend to read:

"10.3. LED module(s): yes/no² and for each LED module a statement whether it is replaceable or not: yes/no² "

Annex 5, paragraph 1.2.1.1., amend to read;

"1.2.1.1. Test mixture

1.2.1.1.1. For front fog lamps with the outside lens in glass:

The mixture of water and a polluting agent to be applied to the front fog lamp shall be composed of:

- (a) 9 parts by weight of silica sand with a particle size of 0-100 µm,
- (b) 1 part by weight of vegetal carbon dust produced from beech wood with a particle size of 0-100 µm,
- (c) 0.2 part by weight of NaCMC⁴,
- (d) 5 parts by weight of sodium chloride (pure at 99 per cent), and
- (e) An appropriate quantity of distilled water with a conductivity of $S < 1 \mu\text{S/m}$.

The mixture must not be more than 14 days old.

1.2.1.1.2. For front fog lamp with outside lens in plastic material:

The mixture of water and polluting agent to be applied to the front fog lamp shall be composed of:

- (a) 9 parts by weight of silica sand with a particle size of 0-100 µm,
- (b) 1 part by weight of vegetal carbon dust produced from beech wood with a particle size of 0-100 µm,
- (c) 0.2 part by weight of NaCMC⁴,
- (d) 5 parts by weight of sodium chloride (pure at 99 per cent),
- (e) 13 parts by weight of distilled water with a conductivity of $S < 1 \mu\text{S/m}$, and
- (f) 2 ± 1 parts by weight of surface-actant. ⁵

The mixture must not be more than 14 days old."

Annex 12, paragraph 4.6., amend to read:

"4.6. UV-radiation

The UV-radiation of a low-UV-type LED module or light-generator shall be such that:

.....

(For definitions of the other symbols see paragraph 4.5.1. above)

This value shall be calculated using intervals of one nanometre. The UV-radiation shall be weighted according to the values as indicated in the UV table below.

λ	$S(\lambda)$	λ	$S(\lambda)$	λ	$S(\lambda)$
250	0.430	305	0.060	355	0.000 16
255	0.520	310	0.015	360	0.000 13
260	0.650	315	0.003	365	0.000 11
265	0.810	320	0.001	370	0.000 09
270	1.000	325	0.000 50	375	0.000 077
275	0.960	330	0.000 41	380	0.000 064
280	0.880	335	0.000 34	385	0.000 053
285	0.770	340	0.000 28	390	0.000 044
290	0.640	345	0.000 24	395	0.000 036
295	0.540	350	0.000 20	400	0.000 030
300	0.300				

UV Table

Values according to other values should be interpolated."

Annex 12, paragraph 4.7.2., amend to read:

"4.7.2. Colour

The colour of the light emitted, measured after 1 minute and measured after photometric stability has been obtained, as described in paragraph 4.7.1.3. of this annex, shall be within the required colour boundaries in both instances."

