

**Economic and Social Council**Distr.: General  
5 February 2018

Original: English

---

**Economic Commission for Europe****Inland Transport Committee****World Forum for Harmonization of Vehicle Regulations****Working Party on Lighting and Light-Signalling****Seventy-ninth session**

Geneva, 24-27 April 2018

Item 4 of the provisional agenda

**Simplification of lighting and light-signalling Regulations****Proposal for Supplement [11] to the 06 series of amendments  
to Regulation No. 48****Submitted by the Informal Working Group on Simplification of  
Lighting and Light-Signalling Regulations (IWG SLR)\***

The text reproduced below was prepared by IWG SLR with the aim to introduce into the 06 series of amendments to Regulation No.48 references to the three new simplified Regulations on Light-Signalling Devices (LSD), Road Illumination Devices (RID) and Retro-Reflective Devices (RRD). It is based on ECE/TRANS/WP.29/GRE/2017/11 as amended by informal document GRE-78-20. The modifications to the existing text of Regulation No. 48 are marked in bold for new or strikethrough for deleted characters. Some text is shown in square brackets to indicate that discussion and a decision are required.

---

\* In accordance with the programme of work of the Inland Transport Committee for 2014–2018 (ECE/TRANS/240, para. 105 and ECE/TRANS/2014/26, cluster 02.4), the World Forum will develop, harmonize and update UN Regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.

GE.18-01664(E)



\* 1 8 0 1 6 6 4 \*

Please recycle The recycling symbol, consisting of three chasing arrows forming a triangle.



## I. Proposal

*Paragraph 3.2.6.2.*, amend to read:

"3.2.6.2. The related AFS control signals and their technical characteristics as defined according to Annex 10 to Regulation No. 123 **or Annex 14 to Regulation No. [RID]**."

*Paragraph 5.9.3.*, amend to read:

"5.9.3. The photometric characteristics of a direction indicator lamp of categories 1, 1a, 1b, 2a or 2b may be varied during a flash by sequential activation of light sources as specified in paragraph 5.6. of Regulation No. 6. **or paragraph 5.6.11. of Regulation No. [LSD]**.

This provision shall not apply when direction indicator lamps of categories 2a and 2b are operated as emergency stop signal according to paragraph 6.23.1. of this Regulation."

*Paragraph 6.1.*, amend to read:

"6.1. Main-beam headlamp (Regulations Nos. 98~~and~~, 112 **and [RID]**)"

*Paragraph 6.1.2.*, amend to read:

"6.1.2. Number

Two or four, type approved according to

- Regulations Nos. 98 or 112, excluding Class A headlamp

**or**

**- Regulation [RID], Classes B and D headlamps only**

For vehicles of the category N3: Two extra main-beam headlamps may be installed.

Where a vehicle is fitted with four concealable headlamps the installation of two additional headlamps shall only be authorized for the purpose of light-signalling, consisting of intermittent illumination, at short intervals (see paragraph 5.12. above) in daylight."

*Paragraph 6.2.*, amend to read:

"6.2. Dipped-beam headlamp (Regulations Nos. 98~~and~~, 112 **and [RID]**)"

*Paragraph 6.2.2.*, amend to read:

"6.2.2. Number

Two, type approved according to

- Regulations Nos. 98 or 112, excluding Class A headlamp,

**or**

**- Regulation [RID], Classes B and D headlamps only."**

*Paragraph 6.2.7.3.*, amend to read:

"6.2.7.3. In the case of dipped-beam headlamps according to Regulations Nos. 98 **or [RID]**, the gas-discharge light sources shall remain switched on during the main-beam operation."

*Paragraph 6.2.9.*, amend to read:

"6.2.9. ...  
 Only dipped-beam headlamps according to Regulations Nos. 98 or 112  
**or [RID]** may be used to produce bend lighting.  
 ..."

*Paragraph 6.3.*, amend to read:

"6.3. Front fog lamp (Regulations Nos. 19 **or [RID]**)"

*Paragraph 6.3.2.*, amend to read:

"6.3.2. Number  
 Two, complying with **either** the requirements of the 03 and subsequent series  
 of amendments to Regulation No. 19 **or the requirements of Regulation  
 No. [RID]**."

*Paragraph 6.3.7.*, amend to read:

"6.3.7. ...  
 (b) The front fog lamps cannot be simultaneously lit with any other lamps  
 with which they are reciprocally incorporated as indicated by the  
 relevant symbol ("/) according to paragraph 10.1. of Annex 1 of  
 Regulation No. 19. **or item 9.5.1. of Annex 1 of Regulation  
 No. [RID]**."

*Paragraph 6.3.9.*, amend to read:

"6.3.9. Other requirements  
 In the case where there is a positive indication in the communication form in  
 item 10.9. of Annex 1 of Regulation No. 19 **or item 9.5.8. of Annex 1 of  
 Regulation No. [RID]** the alignment and the luminous intensities of the class  
 "F3" front fog beam may be automatically adapted in relation to the  
 prevailing ambient conditions. Any variations of the luminous intensities or  
 alignment shall be performed automatically and in such a way that no  
 discomfort, neither for the driver nor to other road users, is caused."

*Paragraph 6.4.*, amend to read:

"6.4. Reversing lamp (Regulations Nos. 23 **or [LSD]**)"

*Paragraph 6.5.*, amend to read:

"6.5. Direction-indicator lamp (Regulations Nos. 6 **or [LSD]**)"

*Paragraph 6.5.8.*, amend to read:

"6.5.8. ...  
 It shall be activated by the signal produced according to paragraph 6.2.2. of  
 Regulation No. 6 **or according to paragraph 5.6.3. of Regulation  
 No. [LSD]** or another suitable way<sup>13</sup>.  
 ..."

*Paragraph 6.7.*, amend to read:

"6.7. Stop lamp (Regulations Nos.7 **or [LSD]**)"

*Paragraph 6.8.*, amend to read:

"6.8. Rear registration plate lamp (Regulations Nos. 4 **or [LSD]**)"

*Paragraph 6.9.*, amend to read:

"6.9. Front position lamp (Regulations Nos. 7 **or [LSD]**)"

*Paragraph 6.10.*, amend to read:

"6.10. Rear position lamp (Regulations Nos. 7 **or [LSD]**)"

*Paragraph 6.11.*, amend to read:

"6.11. Rear fog lamp (Regulations Nos. 38 **or [LSD]**)"

*Paragraph 6.12.*, amend to read:

"6.12. Parking lamp (Regulations Nos. 77 or 7 **or [LSD]**)"

*Paragraph 6.13.*, amend to read:

"6.13. End-outline marker lamp (Regulations Nos. 7 **or [LSD]**)"

*Paragraph 6.14.*, amend to read:

"6.14. Rear retro-reflector, non-triangular (Regulations Nos. 3 **or [RRD]**)"

*Paragraph 6.14.2.*, amend to read:

"6.14.2. Number

Two, the performances of which shall conform to the requirements concerning Class IA or IB retro-reflectors in Regulations Nos. 3 **or [RRD]**. Additional retro-reflecting devices and materials (including two retro-reflectors not complying with paragraph 6.14.4. below), are permitted provided they do not impair the effectiveness of the mandatory lighting and light-signalling devices."

*Paragraph 6.15.*, amend to read:

"6.15. Rear retro-reflector, triangular (Regulations Nos. 3 **or [RRD]**)"

*Paragraph 6.15.2.*, amend to read:

"6.15.2. Number

Two, the performances of which shall conform to the requirements concerning Class IIIA or Class IIIB retro-reflectors in Regulations Nos. 3 **or [RRD]**. Additional retro-reflecting devices and materials (including two retro-reflectors not complying with paragraph 6.15.4. below), are permitted provided they do not impair the effectiveness of the mandatory lighting and light-signalling devices."

*Paragraph 6.16.*, amend to read:

"6.16. Front retro-reflector, non-triangular (Regulations Nos. 3 **or [RRD]**)"

*Paragraph 6.16.2.*, amend to read:

"6.16.2. Number

Two, the performances of which shall conform to the requirements concerning Class IA or IB retro-reflectors in Regulations Nos. 3 **or [RRD]**. Additional retro-reflecting devices and materials (including two retro-reflectors not complying with paragraph 6.16.4. below), are permitted provided they do not impair the effectiveness of the mandatory lighting and light-signalling devices."

*Paragraph 6.17.*, amend to read:

"6.17. Side retro-reflector, non-triangular (Regulations Nos. 3 **or [RRD]**)"

*Paragraph 6.17.2.*, amend to read:

"6.17.2. Number

Such that the requirements for longitudinal positioning are complied with. The performances of these devices shall conform to the requirements concerning Class IA or IB retro-reflectors in Regulations Nos. 3 **or [RRD]**. Additional retro-reflecting devices and materials (including two retro-reflectors not complying with paragraph 6.17.4. below), are permitted provided they do not impair the effectiveness of the mandatory lighting and light-signalling devices."

*Paragraph 6.18.*, amend to read:

"6.18. Side-marker lamps (Regulations Nos. 91 **or [LSD]**)"

*Paragraph 6.19.*, amend to read:

"6.19. Day-time running lamp (Regulations Nos. 87 **or [LSD]**)"

*Paragraph 6.20.*, amend to read:

"6.20. Cornering lamp (Regulations Nos. 119 **or [RID]**)"

*Paragraph 6.21.*, amend to read:

"6.21. Conspicuity markings (Regulations Nos. 104 **or [RRD]**)"

*Paragraph 6.21.1.2.5.*, amend to read:

"6.21.1.2.5. In cases where the manufacturer, after verification by the Technical Service, can prove to the satisfaction of the Type Approval Authority that it is impossible, due to the operational requirements which may require special shape, structure or design of the vehicle, to comply with the requirements contained in paragraphs 6.21.2. to 6.21.7.5. below, then partial fulfilment of some of these requirements is acceptable. This is conditional upon a portion of the requirements being met where possible, and the application of conspicuity markings that partially meet requirements maximised on the vehicle structure. This may include fitting of additional brackets or plates containing material compliant with Regulations Nos. 104 **or [RRD]** where structure is available to ensure clear and uniform signalling compatible with the objective of conspicuity.

Where partial fulfilment is deemed acceptable, retro-reflective devices like retro-reflectors of class IVA of Regulations Nos. 3 **or [RRD]** or brackets containing retro-reflecting material compliant with photometric requirements of Class C of Regulations Nos. 104 **or [RRD]** may substitute part of the required conspicuity markings. In this case, at least one of these retro-reflective devices shall be installed per 1,500 mm.

The necessary information shall be indicated in the communication form."

*Paragraph 6.21.4.2.1.1.*, amend to read:

"6.21.4.2.1.1. For motor vehicles, each end of the vehicle, or in the case of tractors for semi-trailers each end of the cab;

However, an alternative marking mode within 2,400 mm from the front end of the motor vehicle is allowed where a series of retro-reflectors of Class IVA

of Regulations Nos. 3 **or [RRD]** or Class C of Regulations Nos. 104 **or [RRD]** are mounted followed by the required conspicuity marking as follows:

- (a) Retro-reflector size minimum 25 cm<sup>2</sup>;
- (b) One retro-reflector mounted not more than 600 mm from the front end of the vehicle;
- (c) Additional retro-reflectors spaced not more than 600 mm apart;
- (d) The distance between the last retro-reflector and the start of the conspicuity marking shall not exceed 600 mm."

*Paragraph 6.21.7.4.*, amend to read:

"6.21.7.4. Where rear marking plates conforming **either** to the 01 series of amendments to Regulation No. 70 **or to Regulation No. [RRD]** are installed these may be considered, at the discretion of the manufacturer, as part of the conspicuity marking to the rear, for the purposes of calculating the length of the conspicuity marking and its proximity to the side of the vehicle."

*Paragraph 6.22.*, amend to read:

"6.22. Adaptive front lighting system (AFS) (Regulations Nos. 123 **or [RID]**)  
Where not otherwise specified below, the requirements for main-beam headlamps (paragraph 6.1.) and for dipped-beam headlamps (paragraph 6.2.) of this Regulation apply to the relevant part of the AFS."

*Paragraph 6.22.6.1.2.1.*, amend to read:

"6.22.6.1.2.1. In case the passing-beam is generated by several beams from different lighting units, the provisions according to paragraph 6.22.6.1.2. above apply to each said beam's "cut-off" (if any), which is designed to project into the angular zone, as indicated under item 9.4. of the communication form conforming to the model in Annex 1 to Regulations Nos. 123 **or [RID]**."

*Paragraph 6.22.6.3.*, amend to read:

"6.22.6.3. Horizontal orientation:  
For each lighting unit the kink of the elbow of the cut-off line, if any, when projected on the screen, shall coincide with the vertical line through the reference axis of said lighting unit. A tolerance of 0.5 degree to that side which is the side of the traffic direction shall be allowed. Other lighting units shall be adjusted according to the applicant's specification, as defined according to Annex 10 of Regulation No. 123 **or Annex 14 of Regulation No. [RID]**."

*Paragraph 6.22.7.4.3.*, amend to read:

"6.22.7.4.3. (b) In case of a class E mode of the passing-beam which, according to the system's approval documents / communication sheet, complies with a "data set" of Regulation No. 123, Annex 3, Table 6, **or of Regulation No. [RID], Table 14** only.  
Data set E1: The vehicle's speed exceeds 100 km/h (E1-signal applies);  
Data set E2: The vehicle's speed exceeds 90 km/h (E2-signal applies);  
Data set E3: The vehicle's speed exceeds 80 km/h (E3-signal applies)."

*Paragraph 6.22.8.2., amend to read:*

"6.22.8.2. A visual failure tell-tale for AFS is mandatory. It shall be non-flashing. It shall be activated whenever a failure is detected with respect to the AFS control signals or when a failure signal is received in accordance with paragraph 5.9. of Regulation No. 123 **or paragraph 4.13. of Regulation No. [RID]**. It shall remain activated while the failure is present. It may be cancelled temporarily, but shall be repeated whenever the device which starts and stops the engine is switched on and off."

*Paragraph 6.22.8.4., amend to read:*

"6.22.8.4. A tell-tale to indicate that the driver has set the system into a state according to paragraph 5.8. of Regulation No. 123 **or paragraph 4.12. of Regulation No. [RID]** is optional."

*Paragraph 6.22.9.1., amend to read:*

"6.22.9.1. An AFS shall be permitted only in conjunction with the installation of headlamp cleaning device(s) according to Regulation No. 45<sup>18</sup> for at least those lighting units, which are indicated under item 9.3. of the communication form conforming to the model in Annex 1 to Regulation No. 123 **or under item 9.3.3. in Annex 1 to Regulation No. [RID]**, if the total objective luminous flux of the light sources of these units exceeds 2,000 lm per side, and which contribute to the class C (basic) passing-beam."

*Paragraph 6.22.9.5., amend to read:*

"6.22.9.5. The means according to the provisions of paragraph 5.8. of Regulation No 123 **or paragraph 4.12 of Regulation No. [RID]**, which allow the vehicle to be used temporarily in a territory with the opposite direction of driving than that for which approval is sought, shall be explained in detail in the owner's manual."

*Paragraph 6.26., amend to read:*

"6.26. Manoeuvring lamps (Regulations Nos. 23 **or [LSD]**)"

*Paragraph 6.26.9.2., amend to read:*

"6.26.9.2. At the request of the applicant and with the consent of the Technical Service the requirement of 6.26.9.1 may be verified by a drawing or simulation or deemed to be satisfied if the installation conditions comply with paragraph ~~6.2.3-6.2.2.~~ **6.2.2. of Regulation No. 23 or paragraph 5.10.2. of Regulation No. [LSD]**, as noticed in the communication document in Annex 1, paragraph 9."

## II. Justification

1. Since the introduction of Corrigendum 2 to Revision 3 of Regulation No. 48, references to the device regulations have been included into Regulation No. 48.

2. With the new simplified Regulations on LSD, RID and RRD produced by IWG SLR, it is necessary to introduce additional references to Regulation No. 48. This amendment deals with such additional references for the 06 series amendments to Regulation No. 48.