

Proposal for a Corrigendum 2 to Revision 5 to UN Regulation No. 17 and Corrigendum 1 to the 09 series of amendment to UN Regulation No. 17 – SEATS, THEIR ANCHORAGES AND ANY HEAD RESTRAINTS

The text reproduced below has been prepared by the expert from Germany to amend the definition of integrated, detachable and separate head restraint. The modifications to the current text of the Regulation are marked in bold for new or strikethrough for deleted characters.

I. Proposal

Paragraph 6.4.3.5., correct to read:

"6.4.3.5. The distance X, provided for in paragraph ~~5.11.~~ **5.12.** above, between the tangent Y and the displaced reference line is measured."

II. Justification

The reference in paragraph to paragraph 5.11. is wrong. The correct reference is paragraph 5.12.

- 5.11. The width of the head restraint shall be such as to provide appropriate support for the head of a person normally seated. As determined according to the procedure described in paragraph 6.6. below, the head restraint shall cover an area extending not less than 85 mm to each side of the vertical median plane of the seat for which the head restraint is intended.
- 5.12. The head restraint and its anchorage shall be such that the maximum backward displacement X of the head permitted by the head restraint and measured in conformity with the static procedure laid down in paragraph 6.4.3. below, is less than 102 mm.
-