

4 October 2010

Agreement

Concerning the Adoption of Uniform Technical Prescriptions for Wheeled Vehicles, Equipment and Parts which can be Fitted and/or be Used on Wheeled Vehicles and the Conditions for Reciprocal Recognition of Approvals Granted on the Basis of these Prescriptions*

(Revision 2, including the amendments which entered into force on 16 October 1995)

Addendum 6: Regulation No. 7

Revision 5 – Amendment 1

Supplement 16 to the 02 series of amendments to the Regulation: Date of entry into force:
19 August 2010

Uniform provisions concerning the approval of front and rear position lamps, stop-lamps and end-outline marker lamps for motor vehicles (except motor cycles) and their trailers



UNITED NATIONS

* Former title of the Agreement: Agreement Concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Approval for Motor Vehicle Equipment and Parts, don't at Geneva on 20 March 1958.

Paragraph 6.1., the table, amend to read:

“6.1 In the reference axis, the light emitted by each of the two devices supplied must be of not less than the minimum intensity and of not more than the maximum intensity specified below:

	<i>Minimum intensities cd</i>	<i>Maximum values in cd when used as</i>	
		<i>Single lamp</i>	<i>Lamp (single) marked “D” (para. 4.2.2.6.)</i>
6.1.1. Front position lamps, front end-outline marker lamp	4	140	70
6.1.2. Front position lamps incorporated in headlamp	4	140	-
6.1.3. Rear position lamps, rear end-outline marker lamp			
6.1.3.1. R or R1 (steady)	4	17	8.5
6.1.3.2. R2 (variable)	4	42	21
6.1.4. Stop-lamps			
6.1.4.1. S1 (steady)	60	260	130
6.1.4.2. S2 (variable)	60	730	365
6.1.4.3. S3 (steady)	25	110	55
6.1.4.4. S4 (variable)	25	160	80

.”

Paragraph 6.1.5., amend to read:

“6.1.5. For an assembly of two or more lamps the total intensity shall not exceed the maximum value prescribed for a single lamp.”

Paragraph 6.1.6., amend to read:

“6.1.6. When an assembly of two or more lamps having the same function is deemed to be a single lamp, it shall comply with the requirements for:

- (a) Maximum intensity if all lamps together are lit
- (b) Minimum intensity if one lamp has failed.”
