



# Economic and Social Council

Distr.: General  
18 December 2020

Original: English

---

## Economic Commission for Europe

### Inland Transport Committee

### World Forum for Harmonization of Vehicle Regulations

#### 183rd session

Geneva, 9-11 March 2021

Item 4.9.11 of the provisional agenda

#### 1958 Agreement:

Consideration of draft amendments to existing

UN Regulations submitted by GRE

## **Proposal for Supplement 10 to the 01 series of amendments to UN Regulation No. 98 (Headlamps with gas-discharge light sources)**

### **Submitted by the Working Party on Lighting and Light-Signalling\*, \*\***

The text reproduced below was adopted by the Working Party on Lighting and Light-Signalling (GRE) at its eighty-third session (ECE/TRANS/WP.29/GRE/83, para. 42). It is based on ECE/TRANS/WP.29/GRE/2020/11/Rev.1. It is submitted to the World Forum for Harmonization of Vehicle Regulations (WP.29) and to the Administrative Committee (AC.1) for consideration at their March 2021 sessions.

---

\* In accordance with the programme of work of the Inland Transport Committee for 2020 as outlined in proposed programme budget for 2020 (A/74/6 (part V sect. 20) para 20.37), the World Forum will develop, harmonize and update UN Regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.

\*\* This document was scheduled for publication after the standard publication date owing to circumstances beyond the submitter's control.

Paragraph 6.2.5., amend to read:

"6.2.5. After more than 10 minutes after ignition the luminous intensities at the test points referred to in the table below and in Annex 3, Figure B (or mirrored about the VV line for left-hand traffic) shall meet the following requirements:

Points or segments		Designation**						Luminous intensity (cd)		Horizontal angle (degrees)	Vertical angle (degrees)
								Max	Min		
Any point in zone A (bounded by the following coordinates in degrees)											
8L	8L	8R	8R	6R	1,5R	V-V	4L	625			
1U	4U	4U	2U	1,5U	1,5U	H-H	H-H				
1	HV						625		0	0	
2	B 50 L						350		3.43 L	0.57 U	
3	75 R							12,500	1.15 R	0.57 D	
4	50 L						18,480		3.43 L	0.86 D	
5	25 L1						18,800		3.43 L	1.72 D	
6	50 V							7,500	0	0.86 D	
7	50 R							12,500	1.72 R	0.86 D	
8	25 L2							2,500	9 L	1.72 D	
9	25 R1							2,500	9 R	1.72 D	
10	25 L3							1,250	15 L	1.72 D	
11	25 R2							1,250	15 R	1.72 D	
12	15 L							625	20 L	2.86 D	
13	15 R							625	20 R	2.86 D	
14								*	8 L	4 U	
15								*	0	4 U	
16								*	8 R	4 U	
17								*	4 L	2 U	
18								*	0	2 U	
19								*	4 R	2 U	
20								65	8 R	0	
21								125	4 L	0	
A to B	Segment I							3,750	5.15 L to 5.15 R	0.86 D	
C – D							1,750		2.5 R	1 U	
E to F	Segment III and under						12,500		9.37 L to 8.53 R	4.29 D	
	I max R						43,800		Right of VV line	Above 1.72 D	
	I max L						31,300		Left of VV line		

Note: In the table:

Letter L means that the point or segment is located on the left of VV line.

Letter R means that the point or segment is located on the right of VV line.

Letter U means the point or segment is located above HH line.

Letter D means the point or segment is located below HH line

\* The luminous intensities at points 14 through 19 shall be such that:

14 + 15 + 16 ≥ 190 cd and

17 + 18 + 19 ≥ 375 cd.

\*\* For left-hand traffic, the letter R shall be replaced by letter L and vice versa.

..."