

Economic Commission for Europe

Inland Transport Committee

Working Party on the Transport of Dangerous Goods

111th session

Geneva, 9 - 13 May 2022

12 April 2022

Item 4 of the provisional agenda

Work of the RID/ADR/ADN Joint Meeting

Texts adopted by the Joint Meeting: amendments to ADR for entry into force on 1 January 2025

Note by the secretariat

The secretariat reproduces hereafter proposals of amendments to ADR for entry into force on 1 January 2025 as adopted by the Joint Meeting at its March 2022 session (Draft report: ECE/TRANS/WP.15/AC.1/2022/R.2 and adds 1-4 / Final report to be published: ECE/TRANS/WP.15/AC.1/164).

Draft amendments to ADR for entry into force on 1 January 2025

Chapter 3.2, Table A

For UN No. 3082, in column (6), insert "650".

Chapter 3.3

SP 650 Amend as follows:

- In the first sentence, replace "under the conditions of packing group II" by "under the conditions of UN No. 1263, packing group II, or UN No. 3082, as appropriate".
- In the second sentence, replace "provisions of UN No. 1263, packing group II" by "provisions for UN No. 1263 packing group II, and UN No. 3082".
- In paragraph (a), before the semicolon, insert ". Mixed packing of waste classified as UN 1263 and waste water-based paints classified as UN 3082 is permitted".
- In paragraph (d), after the first sentence, insert "Waste classified as UN 1263 may be mixed and loaded with waste water-based paints classified as UN 3082 in the same ~~wagon~~ vehicle or container. In the case of such mixed loading the entire contents shall be assigned to UN 1263."
- In paragraph (e), in the first sentence, after "transport document," insert "with the appropriate UN number(s)".
- In paragraph (e), at the end, add
 ", or
 "UN 3082 WASTE ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT), 9, III (ADR only:), (-)", or
 "UN 3082 WASTE ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT), 9, PG III (ADR only:), (-)""

Chapter 4.3

4.3.2.2.3 Amend to read as follows:

“4.3.2.2.3 The provisions of 4.3.2.2.1 (a) to (d) above shall not apply to tanks carrying liquids at a temperature above 50 °C.

The degree of filling of:

- liquid substances carried at a temperature above 50 °C;
- liquid substances filled below 50 °C but intended to be heated above 50 °C during the carriage operation; and
- solid substances carried above their melting point;

shall at the outset be such that the tank is not more than 95 % full at any time during carriage.

The maximum degree of filling shall be determined by the following formula:

$$\text{Degree of filling} = 95 \frac{d_r}{d_f} \% \text{ of capacity}$$

in which d_r and d_f are the densities of the substance at the mean temperature during filling and the maximum mean bulk temperature during carriage respectively.

Tanks with a heating device shall have the temperature so regulated that the maximum degree of filling of 95 % of capacity is not exceeded at any time during carriage.”

Chapter 6.8

~~(ADR:)~~

6.8.2.1.20 In the left-hand column, in paragraph (b) 1., in the first paragraph, replace “strengthening members” by “strengthening elements”.

In the left-hand column, in paragraph (b) 1., in the last paragraph, after “surge plates”, insert “that are used as strengthening elements”.
