



Economic and Social Council

Distr.: General
19 December 2022

Original: English

Economic Commission for Europe

Inland Transport Committee

World Forum for Harmonization of Vehicle Regulations

189th session

Geneva, 7-9 March 2023

Item 4.6.5 of the provisional agenda

1958 Agreement:

Consideration of draft amendments to existing

UN Regulations submitted by GRBP

Proposal for Supplement 1 to the 03 series of amendments to UN Regulation No. 117 (Tyre rolling resistance, rolling noise and wet grip)

Submitted by the Working Party on Noise and Tyres*

The text reproduced below was adopted by the Working Party on Noise and Tyres (GRBP) at its seventy-sixth session (ECE/TRANS/WP.29/GRBP/74, paras. 21 and 26). It is based on ECE/TRANS/WP.29/GRBP/2022/22, as amended by GRBP-76-05 and GRBP-76-34, and ECE/TRANS/WP.29/GRBP/2022/18. It is submitted to the World Forum for Harmonization of Vehicle Regulations (WP.29) and to the Administrative Committee (AC.1) for consideration at their March 2023 sessions.

* In accordance with the programme of work of the Inland Transport Committee for 2023 as outlined in proposed programme budget for 2023 (A/77/6 (Sect. 20), table 20.6), the World Forum will develop, harmonize and update UN Regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.

Table of contents, Annexes, amend to read:

"7 Procedures for snow performance testing relative to tyres for use in severe snow conditions...
[...]"

Paragraph 2.1., subparagraph (e), amend to read:

" (e) Whether tyre for use in severe snow conditions or not;"

Paragraph 2.13.1., amend to read:

"2.13.1. "Tyre for use in severe snow conditions" means a snow tyre or a special use tyre whose tread pattern, tread compound or structure is specifically designed to be used in severe snow conditions and that fulfils the requirements of paragraphs 6.5. and 6.5.1. of this Regulation.

2.13.1.1. "Ice grip tyre" means a class C1 snow tyre that is classified as tyre for use in severe snow conditions and additionally designed to be used on road surfaces covered with ice and that fulfils the requirements of paragraph 6. 5.2. of this Regulation."

Paragraph 2.18., amend to read:

"2.18. [...]
(c) F3611-22 for the size P225/60R16 in worn state and referred to as "moulded SRTT16 worn",
(d) F2872 – 16 for the size 225/75R16C and referred to as "SRTT16C",
(e) F2871 – 16 for the size 245/70R19.5 and referred to as "SRTT19.5",
(f) F2870 – 16 for the size 315/70R22.5 and referred to as "SRTT22.5"."

Paragraph 3.1.1., amend to read:

"3.1.1. The performance characteristics to be assessed for the type of tyre; "rolling sound emissions level" and/or "adhesion performance level on wet surfaces" of a tyre in new state" and/or "adhesion performance level on wet surfaces of a tyre in worn state" and/or "rolling resistance level"; "snow performance level" in case of tyre for use in severe snow conditions and additionally "ice performance level" in case of ice grip tyre;"

Paragraph 3.1.5.1., amend to read:

"3.1.5.1. Whether tyre for use in severe snow conditions or not;"

Paragraph 4.2.6., amend to read:

"4.2.6. The "Alpine Symbol" ("3-peak-mountain with snowflake" conforming to the pictogram described in Annex 7, Appendix 1) if the snow tyre or the special use tyre is classified as tyre for use in severe snow conditions;"

Paragraph 4.2.6.1., amend to read:

"4.2.6.1. The "Ice Grip Symbol" (conforming to the pictogram described in Annex 8, Appendix 1) if the tyre for use in severe snow conditions is additionally classified as ice grip tyre;"

Add a new paragraph 4.2.6.2., to read:

"4.2.6.2. The inscription "M+S" or "M.S" or "M&S" if the special use tyre is classified as tyre for use in severe snow conditions in addition to the "Alpine Symbol";"

Paragraph 6.1.1., footnote below the table of limits for Stage 2, amend to read:

"The above limits shall be increased by 1 dB(A) for snow tyres that are classified as tyre for use in severe snow conditions, extra load tyres or reinforced tyres, or any combination of these classifications."

Paragraph 6.1.2., table of limits for Stage 2, amend to read:

"

Stage 2		
Category of use	Limit dB(A)	
	Other	Traction tyres
Normal tyre	72	73
Snow tyre	72	73
	Snow tyre that is classified as tyre for use in severe snow conditions	73
Special use tyre	74	75
	Special use tyre that is classified as tyre for use in severe snow conditions	74

"

Paragraph 6.1.3., table of limits for Stage 2, amend to read:

"

Stage 2		
Category of use	Limit dB(A)	
	Other	Traction tyres
Normal tyre	73	75
Snow tyre	73	75
	Snow tyre that is classified as tyre for use in severe snow conditions	74
Special use tyre	75	77
	Special use tyre that is classified as tyre for use in severe snow conditions	75

"

Paragraph 6.2.1., table of limits, amend to read:

"

Category of use	Wet grip index (G)	
Normal tyre	≥ 1.1	
Snow tyre	≥ 1.1	
	Snow tyre that is classified as tyre for use in severe snow conditions and with a speed symbol ("R" and above, including "H") indicating a maximum permissible speed greater than 160 km/h	≥ 1.0
	Snow tyre that is classified as tyre for use in severe snow conditions and with a speed symbol ("Q" or below excluding "H")	≥ 0.9

	indicating a maximum permissible speed not greater than 160 km/h	
Special use tyre		Not defined
	Special use tyre that is classified as tyre for use in severe snow conditions	Not defined

"

Paragraph 6.2.2., table of limits, amend to read:

"

Category of use	Wet grip index (G)	
	Other	Traction tyres
Normal tyre	≥ 0.95	≥ 0.85
Snow tyre	≥ 0.95	≥ 0.85
	Snow tyre that is classified as tyre for use in severe snow conditions	≥ 0.85
Special use tyre	≥ 0.85	≥ 0.85
	Special use tyre that is classified as tyre for use in severe snow conditions	≥ 0.85

"

Paragraph 6.2.3., table of limits, amend to read:

"

Category of use	Wet grip index (G)	
	Other	Traction tyres
Normal tyre	≥ 0.80	≥ 0.65
Snow tyre	≥ 0.65	≥ 0.65
	Snow tyre that is classified as tyre for use in severe snow conditions	≥ 0.65
Special use tyre	≥ 0.65	≥ 0.65
	Special use tyre that is classified as tyre for use in severe snow conditions	≥ 0.65

"

Paragraph 6.3., last sentence, amend to read:

"... For snow tyres that are classified as tyre for use in severe snow conditions, the limits shall be increased by 1 N/kN."

Paragraph 6.4.1, table of limits, amend to read:

"

Category of use	Wet grip index (G _B)
Normal tyre	≥ 0.88
Snow tyre	≥ 0.80
	Snow tyre that is classified as tyre for use in severe snow conditions

Category of use		Wet grip index (G_B)	
	and with a speed category symbol ("R" and above, including "H") indicating a maximum permissible speed-greater than 160 km/h	Ice grip tyre ≥ 0.70	
	Snow tyre that is classified as tyre for use in severe snow conditions and with a speed category symbol ("Q" or below excluding "H") indicating a maximum permissible speed not greater than 160 km/h		≥ 0.70
		Ice grip tyre	≥ 0.70
Special use tyre		Not defined	
	Special use tyre that is classified as tyre for use in severe snow conditions	Not defined	

For normal tyres with speed category symbol indicating a maximum permissible speed equal to or greater than 300 km/h and aspect ratio equal to or lower than 40, the limit shall be decreased by 0.08."

Paragraph 6.5., amend to read:

"6.5. In order to be classified as a tyre for use in severe snow conditions the tyre shall meet the performance requirements of paragraph 6.5.1. below. The tyre shall meet these requirements based on a test method of Annex 7 by which:

[...]"

Paragraph 6.5.2., replace "a snow tyre for use" by "a tyre for use".

Paragraph 12., insert new subparagraphs 12.9., 12.10. and 12.11., to read:

"12.9. Until 6 July 2024, Contracting Parties applying this Regulation may continue to grant type approvals of class C1 tyres according to the 03 series of amendments to this Regulation, based on the test procedures for measuring the wet adhesion of tyres in worn state as described in Annex 9 to this Regulation using buffed SRTT16 in worn state as reference tyre.

12.10. Notwithstanding paragraph 12.9., Contracting Parties applying this Regulation shall continue to grant extensions to existing type approvals of class C1 tyres according to the 03 series of amendments to this Regulation first granted before 7 July 2024, based on the test procedures for measuring the wet adhesion of tyres in worn state as described in Annex 9 to this Regulation using buffed SRTT16 in worn state as reference tyre. In case a new test has to be performed on a different representative tyre size for an extension to be granted after 7 July 2024, the moulded SRTT16 worn shall be used.

12.11. Until 60 months from the entry into force of Supplement 15 to the 02 series of amendments, Contracting Parties applying this Regulation shall continue to grant type approvals and extension to existing type approvals according to the 03 series of amendments to this Regulation, based on tyre-rolling sound emissions tests performed on test sites the surface and the dimensions of which are in accordance with ISO 10844:2014."

Annex 1,

Item 4.1, amend to read:

"4.1. Tyre for use in severe snow conditions (Yes/No)²"

Item 8.3., amend to read:

"8.3. Wet adhesion level of tyres in worn state of representative size, see paragraph 2.7. of this Regulation, as per the test report in the appendix to Annex 9: (G_B) using the vehicle or trailer method²"

Footnote 6, amend to read:

"⁶ In the case of tyre for use in severe snow conditions a test report according to Appendix 2 or Appendix 3, as applicable, to Annex 7 shall be submitted. Additionally in the case of ice grip tyre a test report according to Appendix 2 to Annex 8 shall be submitted."

Annex 3,

Paragraph 2.1., replace "ISO 10844:2014" by "ISO 10844:2021".

Appendix 1, item 6.1, amend to read:

"6.1. Tyre for use in severe snow conditions (Yes/No)¹"

Annex 5, part (A),

Paragraph 3.3., table of temperatures, amend to read:

"

Category of use		Wetted surface temperature	Ambient temperature
Normal tyre		12 °C – 35 °C	12 °C – 40 °C
Snow tyre		5 °C – 35 °C	5 °C – 40 °C
	Snow tyre that is classified as tyre for use in severe snow conditions	5 °C – 20 °C	5 °C – 20 °C
Special use tyre		not applicable	not applicable
	Special use tyre that is classified as tyre for use in severe snow conditions	not applicable	not applicable

"

Paragraph 4.1.6.4., table 2, amend to read:

"

Table 2

Category of use	ϑ_0 (°C)	a	b (°C ⁻¹)	c (°C ⁻²)	d (mm ⁻¹)	
Normal tyre	20	+0.99382	+0.00269	-0.00028	-0.02472	
Snow tyre	15	+0.92654	-0.00121	-0.00007	-0.04279	
	Snow tyre that is classified as tyre for use in severe snow conditions	10	+0.72029	-0.00539	+0.00022	-0.03037
Special use tyre	not defined					
	Special use tyre that is classified as tyre for use in severe snow conditions	not defined				

"

Paragraph 4.2.8.4., table 4, amend to read:

" Table 4

Category of use	ϑ_0 (°C)	a	b (°C ⁻¹)	c (°C ⁻²)	d (mm ⁻¹)
Normal tyre	20	+0.99757	+0.00251	-0.00028	+0.07759
Snow tyre	15	+0.87084	-0.00025	+0.00004	-0.01635
Snow tyre that is classified as tyre for use in severe snow conditions	10	+0.67929	+0.00115	-0.00005	+0.03963
Special use tyre	not defined				
Special use tyre that is classified as tyre for use in severe snow conditions	not defined				

Annex 5, part (B),

Paragraph 2.1.2.1., amend to read:

"2.1.2.1. [...]

$$P_t = P_r \cdot \left(\frac{Q_t}{Q_r}\right)^{1.25}$$

Where:

P_r = Inflation pressure corresponding to the indication of the inflation pressure marked on the sidewall as required by paragraph 4.1. of this Regulation.

Q_t = The static test load of the tyre

Q_r = The maximum mass associated with the load capacity index of the tyre."

Annex 6,

Appendix 3, item 6.1, amend to read:

"6.1. Tyre for use in severe snow conditions (Yes/No)²"

Annex 7,

Title, amend to read:

"Procedures for snow performance testing relative to tyres for use in severe snow conditions"

Paragraph 3.1.4.2., amend to read:

"3.1.4.2. For class C2 tyres, the vehicle load shall be such that the resulting loads on the tyres are between 60 per cent and 100 per cent of the load corresponding to the tyre load capacity index.

[...]

$$P_t = P_r \cdot \left(\frac{Q_t}{Q_r}\right)^{1.25}$$

Q_r is the maximum load associated to the load capacity index of the tyre written on the sidewall

P_r is the inflation pressure corresponding to the indication of the inflation pressure marked on the sidewall as required by paragraph 4.1. of this Regulation.

Q_i is the static test load of the tyre

For a vertical load lower than 75 per cent of the load capacity of the tyre, a constant inflation pressure is applied, hence the test inflation pressure P_t shall be calculated as follows:

$$P_t = P_r \times (0.75)^{1.25} = 0.7 P_r$$

P_r is the inflation pressure corresponding to the indication of the inflation pressure marked on the sidewall as required by paragraph 4.1. of this Regulation.

Check the tyre pressure just prior to testing at ambient temperature."

Annex 8,

Title, amend to read:

"Procedures for ice performance testing relative to ice grip tyres of class C1"

Paragraph 2.4.2.2., Table 3, amend to read:

"Table 3

Calculation of the adjusted mean fully developed deceleration $d_{m,adj}(R)$ of the reference tyre

<i>If the number and the sequence of candidate tyres within one braking test cycle is</i>	<i>and the candidate tyre to be qualified is</i>	<i>the corresponding adjusted mean fully developed deceleration $d_{m,adj}(R)$ of the reference tyre is calculated as follows</i>
1 $R_i - T_1 - R_f$	T_1	$d_{m,adj}(R) = 1/2 \cdot [d_{m,ave}(R_i) + d_{m,ave}(R_f)]$
2 $R_i - T_1 - T_2 - R_f$	T_1	$d_{m,adj}(R) = 2/3 \cdot d_{m,ave}(R_i) + 1/3 \cdot d_{m,ave}(R_f)$
	T_2	$d_{m,adj}(R) = 1/3 \cdot d_{m,ave}(R_i) + 2/3 \cdot d_{m,ave}(R_f)$

"

Second occurrence of paragraph 2.4.2.2., renumber as 2.4.2.3.

Second occurrence of paragraph 2.4.4.4., renumber as 2.4.4.5.

Paragraph 2.4.4.5. (former), renumber as 2.4.4.6.

Paragraph 2.4.5.2.1., replace "2.4.4.5." by "2.4.4.6."

Annex 9,

Paragraph 2.1.1., amend to read:

"2.1.1. "Tyre in worn state" or "worn tyre" means, for the purpose of this Regulation, a new tyre artificially worn by reducing the tread depth or, with respect to the reference tyre in worn state, moulded at the height defined in paragraph 2.2.1.2.4.1. of this Annex."

Paragraph 2.1.13., amend to read:

"2.1.13. "Reference tyre in worn state" or "Reference tyre set in worn state" means a tyre or a tyre set of Standard Reference Test Tyres moulded SRTT16 worn. "

Insert a new paragraph 2.2.1.2.4.1.1., to read:

"2.2.1.2.4.1.1. The rim width shall be one specified by a recognized tyre and rim standards organization as listed in Appendix 4 to Annex 6 to this Regulation. The rim width code shall not differ by more than 0.5 from the measuring rim width code. "

Insert a new paragraph 2.2.1.2.4.1.2., to read:

"2.2.1.2.4.1.2. The inflation pressure for the tread depth measurement shall be between 180 kPa and 220 kPa. "

Paragraph 2.3.1.5., replace "SRTT16 in worn state" by "moulded SRTT16 worn".

Paragraph 2.3.3., table of temperatures, amend to read:

"

Category of use		Wetted surface temperature	Ambient temperature
Normal tyres		12 °C – 35 °C	12 °C – 40 °C
Snow tyres		5 °C – 35 °C	5 °C – 40 °C
	Snow tyre that is classified as tyre for use in severe snow conditions	5 °C – 20 °C	5 °C – 20 °C
Special use tyres		not applicable	not applicable
	Special use tyre that is classified as tyre for use in severe snow conditions	not applicable	not applicable

"

Paragraph 2.4.1.1.4., amend to read:

"2.4.1.1.4. Calculation of the wet grip index of the candidate tyre

[...]

$BFC_{adj}(R)$ is the adjusted average braking force coefficient in accordance with Table 1 of Annex 5;

[...]

$K_{vehicle} = 1.95$ is a factor to grant consistency between previous calculation of the wet grip index and this one, and to ensure convergence between vehicle and trailer method and

coefficients a , b , c and d are given in Table 2.

Table 2

Category of use	g_0 (°C)	a	b (°C ⁻¹)	c (°C ⁻²)	d (mm ⁻¹)	
Normal tyre	20	+0.90996	-0.00179	-0.00013	-0.10313	
Snow tyre	15	+0.81045	-0.00004	-0.00019	-0.05093	
	Snow tyre that is classified as tyre for use in severe snow conditions	10	+0.71094	+0.00172	-0.00025	+0.00127
Special use tyre	not defined					

Category of use		g_0 (°C)	a	b (°C ⁻¹)	c (°C ⁻²)	d (mm ⁻¹)
	Special use tyre that is classified as tyre for use in severe snow conditions	not defined				

Paragraph 2.4.2.1.4., amend to read:

"2.4.2.1.4. Calculation of the wet grip index of the candidate tyre

[...]

$\mu_{\text{peak,adj}}(\mathbf{R})$ is the adjusted peak braking force coefficient in accordance with Table 3 of Annex 5;

[...]

$K_{\text{trailer}} = 1.50$ is a factor to grant consistency between previous calculation of the wet grip index and this one, and to ensure convergence between vehicle and trailer method and

coefficients a , b , c and d are given in Table 4.

Table 4

Category of use		g_0 (°C)	a	b (°C ⁻¹)	c (°C ⁻²)	d (mm ⁻¹)
Normal tyre		20	+0.99655	-0.00124	+0.00041	+0.06876
Snow tyre		15	+0.94572	-0.00032	-0.00020	+0.08047
	Snow tyre that is classified as tyre for use in severe snow conditions	10	+0.89488	+0.00061	-0.00080	+0.09217
Special use tyre		not defined				
	Special use tyre that is classified as tyre for use in severe snow conditions	not defined				