



# Economic and Social Council

Distr.: General  
23 December 2022

Original: English

---

## Economic Commission for Europe

### Inland Transport Committee

### World Forum for Harmonization of Vehicle Regulations

#### 189th session

Geneva, 7-9 March 2023

Item 4.14.1 of the provisional agenda

#### 1958 Agreement:

**Proposal for amendments to the Consolidated Resolution**

**on the common specification of light source categories (R.E.5)**

## **Proposal for Amendment 9 to the Consolidated Resolution on the common specification of light source categories (R.E.5)**

### **Submitted by the Working Party on Lighting and Light-Signalling\***

The text reproduced below was adopted by the Working Party on Lighting and Light-Signalling (GRE) at its eighty-seventh session (ECE/TRANS/WP.29/GRE/87, para. 14). It is based on ECE/TRANS/WP.29/GRE/2022/26. It is submitted to the World Forum for Harmonization of Vehicle Regulations (WP.29) and to the Administrative Committee (AC.1) for consideration at their March 2023 sessions.

---

\* In accordance with the programme of work of the Inland Transport Committee for 2023 as outlined in proposed programme budget for 2023 (A/77/6 (Sect. 20), table 20.6), the World Forum will develop, harmonize and update UN Regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.



The Status table, amend to read:

### "Status table

This consolidated version of this Resolution contains all provisions and amendments adopted so far by the World Forum for Harmonization of Vehicle Regulations (WP.29) and is valid from the date as indicated in the following table until the date on which the next revision of this Resolution becomes valid:

Version of the Resolution	Date * as from which the version is valid	Adopted by WP.29		Clarification
		Session No.	Amendment document No.	
1 (Original)	22.06.2017	170	ECE/TRANS/WP.29/2016/111	Based upon Annexes 1 of UN Regulations: <ul style="list-style-type: none"> <li>No. 37, up to and including Supplement 44</li> <li>No. 99, up to and including Supplement 11</li> <li>No. 128, up to and including Supplement 5</li> </ul>
...	...	...	...	...
9	08.03.2023	189	ECE/TRANS/WP.29/2023/41	Amended detail in sheets: H19/1, H19/2, H19/4, H19/5, L1/5  Amended detail in LED light source sheet LR4/2  Introduction of new LED light source categories LW6A, LW6B, LY6A and LY6B

\* This date is the date of adoption of the amendment to the Resolution by WP.29 or the date of entering into force of an amendment to UN Regulation No. 37, 99 or 128 adopted by AC.1 as a package with the amendment to the Resolution in the same session of WP.29.

Paragraph 3.3.,

Group 2, amend to read:

"

Group 2			
LED light source categories only for use in signalling lamps, cornering lamps, reversing lamps and rear registration plate lamps:			
	Category		Sheet number(s)
	LR1		LR1/1 to 5
	LW2	<sup>2</sup>	LW2/1 to 5
	LR3A		Lx3/1 to 6
	LR3B		Lx3/1 to 6
	LW3A	<sup>2</sup>	Lx3/1 to 6
	LW3B	<sup>2</sup>	Lx3/1 to 6
	LY3A		Lx3/1 to 6
	LY3B		Lx3/1 to 6
	LR4A		LR4/1 to 5
	LR4B		LR4/1 to 5
	LR5A		Lx5/1 to 6
	LR5B		Lx5/1 to 6
	LW5A	<sup>2</sup>	Lx5/1 to 6
	LW5B	<sup>2</sup>	Lx5/1 to 6
	LY5A		Lx5/1 to 6
	LY5B		Lx5/1 to 6

<i>Group 2</i>			
<i>LED light source categories only for use in signalling lamps, cornering lamps, reversing lamps and rear registration plate lamps:</i>			
	<i>Category</i>		<i>Sheet number(s)</i>
	LR6A		Lx6/1 to 6
	LR6B		Lx6/1 to 6
	LW6A	<sup>2</sup>	Lx6/1 to 6
	LW6B	<sup>2</sup>	Lx6/1 to 6
	LY6A		Lx6/1 to 6
	LY6B		Lx6/1 to 6

<sup>1</sup> Not for use in conformity of production control of lamps.

<sup>2</sup> Not for use behind red and amber lenses"

*Annex 1,*

*Sheet H19/1, the introductory text above the figures, amend to read:*

"The drawings are intended only to illustrate the essential dimensions (in mm) of the filament light source."

*Sheet H19/1, the caption with Figure 2, amend to read:*

"Figure 2 - Maximum filament light source outline<sup>4</sup>"

*Sheet H19/2, table, header row, amend to read:*

"...

<i>Dimensions in mm</i>	<i>Filament light sources of normal production</i>	<i>Standard filament light sources</i>
	<i>12 V</i>	<i>12 V</i>

..."

*Sheet H19/4, table, header row, amend to read:*

"...

<i>Reference*</i>	<i>Dimension**</i>	<i>Tolerance</i>	
		<i>Filament light sources of normal production</i>	<i>Standard filament light sources</i>

..."

*Sheet H19/5, footnote 3, amend to read:*

"...

<sup>3</sup> The light emitted from standard filament light sources and from normal production filament light sources shall be white.

..."

*Annex 3,*

*Sheet L1/5, table 3, caption, amend to read:*

"Test point values of normalized intensities of normal production and standard LED light sources, respectively"


*Annex 3, Sheet LR4/2, table 1, footnote 9, amend to read:*

"<sup>9/</sup> Light centre length, both functions are operated at the same time during the measurement; for the method of measurement, see Annex K of IEC Publication 60809, Edition 4."


*Annex 3, Sheets Lx6/1 to 6, amend to read (see following pages; one page per sheet):*

The drawings are intended only to illustrate the essential dimensions of the LED light source.


Figure 1\*  
Main Drawing



**LR6A, LW6A, LY6A**



**LR6B, LW6B, LY6B**

\* Projection method: 

For the notes see sheet Lx6/2

## Categories LR6A, LR6B, LW6A, LW6B, LY6A, LY6B

Sheet Lx6/2

Table 1  
Essential dimensional, electrical and photometric characteristics of the LED light source

Dimensions		Production LED light sources	Standard LED light sources	
a	mm	6.0 max.		
b	mm	c + 10.0 min. 38.0 max.		
c	mm	18.5 ± 0.1		
d	mm	28.0 max.		
e <sup>8/</sup>	mm	3.0 ± 0.30	3.0 ± 0.15	
k <sup>9/</sup>	mm	7.5 min.		
m <sup>9/</sup>	mm	4.0 max.		
Cap	LR6A, LR6B LW6A, LW6B LY6A, LY6B	PGJ18.5d-33 PGJ18.5d-12 PGJ18.5d-7	in accordance with IEC Publication 60061 (sheet 7004-185-3)	
<i>Electrical and photometric characteristics</i>				
Rated values	Volts	12		
	Watts	LR6A, LR6B	7	
		LW6A, LW6B	7	
LY6A, LY6B		7		
Test voltage	Volts (DC)	13.5		
Objective Values <sup>6</sup>	Watts (at test voltage)	LR6A, LR6B	8 max.	
		LW6A, LW6B	8 max.	
		LY6A, LY6B <sup>10</sup>	8 max.	
	Luminous flux (in lm at test voltage) <sup>5</sup>	LR6A, LR6B	180 ± 15%	180 ± 10% <sup>7</sup>
		LW6A, LW6B	550 ± 20%	550 ± 10% <sup>7</sup>
		LY6A, LY6B <sup>10</sup>	440 ± 20%	440 ± 10% <sup>7</sup>
	Luminous flux (in lm at 9 V DC) <sup>5</sup>	LR6A, LR6B	40 min.	
LW6A, LW6B		110 min.		
LY6A, LY6B <sup>10</sup>		90 min.		

<sup>1/</sup> The reference plane is the plane defined by the contact points of the cap-holder fit.

<sup>2/</sup> The reference axis is perpendicular to the reference plane and passing through the centre of the bayonet core.

<sup>3/</sup> Light emitting area: to be checked by means of the box system in Figure 2

<sup>4/</sup> A minimum free air space of 5 mm around the light source shall be respected for convection; the connector interface can be neglected.

<sup>5/</sup> The emitted light shall be red for LR6A and LR6B, white for LW6A and LW6B, and amber for LY6A and LY6B.

<sup>6/</sup> After continuous operation for 30 minutes at 23 ± 2.5° C.

<sup>7/</sup> The measured value shall be in between 105 per cent and 90 per cent of the value measured after 1 minute.

<sup>8/</sup> Light centre length; for the method of measurement, see Annex K of IEC 60809, Edition 4.

<sup>9/</sup> The bounded area defined with the dimensions c, k and m defines the maximum outline in relation to the reference system

<sup>10/</sup> Operated in flashing mode for 30 minutes (frequency = 1.5 Hz, duty cycle 50 per cent ON, 50 per cent OFF). Measured in the ON-state of flashing mode after 30 minutes of operation.

## Electrical characteristics

In case of LED light source failure (no light emitted) the max. electrical current draw, when operated between 12 V and 14 V, shall be less than 20 mA (open circuit condition).



CATEGORIES LR6A, LR6B, LW6A, LW6B, LY6A, LY6B

Table 3  
**Proportion of the total luminous flux emitted into the viewing direction from the areas specified in Figure 2**

<i>Category</i>	<i>Area(s)</i>	<i>LED light sources of normal production</i>	<i>Standard LED light sources</i>
LR6A, LR6B LY6A, LY6B	Each A individually	> 3% < 10 %	> 4% < 10%
	Each B individually	> 3% < 10%	> 3% < 10%
	All A and B together	> 70%	> 75%
	Each C individually	< 2%	< 2%
	All A, B and C together	> 90%	> 90%
LW6A, LW6B	Each A individually	> 3% < 10 %	> 3% < 10%
	Each B individually	> 3% < 10%	> 3% < 10%
	All A and B together	> 65%	> 70%
	Each C individually	< 3%	< 3%
	All A, B and C together	> 90%	> 90%

Normalized luminous intensity distribution

The following test is intended to determine the normalized luminous intensity distribution of the light source in an arbitrary plane containing the reference axis. The intersection of the reference axis and the parallel plane to the reference plane in distance  $e = 3.0 \text{ mm}$  is used as the coordinate system origin.

The light source is mounted on a flat plate with the corresponding mounting lug features. The plate is mounted to the goniometer table by a bracket, so that the reference axis of the light source lines up with one of the rotating axes of the goniometer. The corresponding measurement set-up is described in Figure 3.

Luminous intensity data is recorded with a standard photo-goniometer. The measurement distance should be chosen appropriately, to make sure that the detector is located in the far field of the light distribution.



The measurements shall be performed in C-planes  $C_0$ ,  $C_{90}$ ,  $C_{180}$  and  $C_{270}$ , which contain the reference axis of the light source. The test points for each plane for multiple polar angles  $\gamma$  are specified in Table 4.

The measured luminous intensity values, normalised to the measured luminous flux of the individual light source under test, shall be converted to normalised luminous intensity values of a 1,000 lm light source. The data shall comply with the tolerance band as defined in Table 4.

The drawings are intended only to illustrate the essential set-up for measurement of the LED light source.

Figure 3

Set-up to measure the luminous intensity distribution



The light pattern as described in Table 4 shall be substantially uniform, i.e. in between two adjacent grid points the relative luminous intensity requirement is calculated by linear interpolation using the two adjacent grid points. In case of doubt this may be checked in addition to verification of the grid points given in Table 4.

Table 4

**Test point values of normalized intensities**

<i>Angle <math>\gamma</math></i>	<i>LED light sources of normal production</i>		<i>Standard LED light sources</i>	
	<i>Minimum Intensity in cd /1000 lm</i>	<i>Maximum Intensity in cd/1000 lm</i>	<i>Minimum Intensity in cd /1000 lm</i>	<i>Maximum Intensity in cd /1000 lm</i>
0°	200	425	250	390
15°	190	415	240	370
30°	170	380	220	335
45°	145	310	180	275
60°	85	245	105	220
75°	0	160	0	150
90°	0	70	0	65

"