

26 November 2021

---

## Agreement

### **Concerning the Adoption of Harmonized Technical United Nations Regulations for Wheeled Vehicles, Equipment and Parts which can be Fitted and/or be Used on Wheeled Vehicles and the Conditions for Reciprocal Recognition of Approvals Granted on the Basis of these United Nations Regulations\***

(Revision 3, including the amendments which entered into force on 14 September 2017)

---

#### **Addendum 29 – UN Regulation No. 30**

#### **Revision 3 - Amendment 9**

Supplement 23 to the 02 series of amendments – Date of entry into force: 30 September 2021

#### **Uniform provisions concerning the approval of pneumatic tyres for motor vehicles and their trailers**

This document is meant purely as documentation tool. The authentic and legal binding text is: ECE/TRANS/WP.29/2021/2.



**UNITED NATIONS**

---

\* Former titles of the Agreement:

Agreement concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Approval for Motor Vehicle Equipment and Parts, done at Geneva on 20 March 1958 (original version); Agreement concerning the Adoption of Uniform Technical Prescriptions for Wheeled Vehicles, Equipment and Parts which can be Fitted and/or be Used on Wheeled Vehicles and the Conditions for Reciprocal Recognition of Approvals Granted on the Basis of these Prescriptions, done at Geneva on 5 October 1995 (Revision 2).



*Paragraph 3.4.*, amend to read:

"3.4. The markings referred to in paragraph 3.1. and the approval mark prescribed in paragraph 5.4 of this Regulation shall be clearly legible, indelible and raised above or sunk below the tyre surface."

*Paragraph 3.4.1.*, amend to read:

"3.4.1. The markings shall be situated in the lower area of the tyre on at least one of its sidewalls, except for the inscriptions mentioned in paragraphs 3.1.1., 3.1.2. and 3.1.12.

However, for tyres identified by the "tyre to rim fitment configuration" (see para. 2.27.1.), symbol "A" or "U", the markings may be placed anywhere on the outside sidewall of the tyre."

*Insert a new paragraph 3.4.2.*, to read:

"3.4.2. In the case that the date of manufacture is not moulded, it shall be applied not later than 24 hours after the tyre is removed from the mould."

---