

Economic and Social Council

Distr.: General 23 July 2024

Original: English

Economic Commission for Europe

Inland Transport Committee

World Forum for Harmonization of Vehicle Regulations

Working Party on Pollution and Energy

Ninety-first session Geneva, 14–16 October 2024 Item 6 (a) of the provisional agenda Agricultural and forestry tractors, non-road mobile machinery: UN Regulations No. 96 (Diesel emission (agricultural tractors)) 120 (Net power of tractors and non-road mobile machinery)

> Proposal for a new Supplement to the 05 series of amendments to UN Regulation No. 96 (Uniform provisions concerning the approval of engines to be installed in agricultural and forestry tractors and in nonroad mobile machinery with regard to the emissions of pollutants by the engine)

Submitted by the expert from France*

The text reproduced below was prepared by the experts from France and proposes to correct editorial errors to the text of Supplement 1 to the 05 series of amendments to UN Regulation No. 96. The modifications to the current text of the Regulation are marked in bold for new or strikethrough for deleted characters.

^{*} In accordance with the programme of work of the Inland Transport Committee for 2024 as outlined in proposed programme budget for 2024 (A/78/6 (Sect. 20), table 20.5), the World Forum will develop, harmonize and update UN Regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.

I. Proposal

Annex 2 Appendix A.1, paragraph 10.3.1., amend to read:

"10.3.1. Hot cycle Cycle weighted CO_2 (g/kWh) (⁷):"

Annex 2 Appendix A.1, paragraph 10.3.4., amend to read:

"10.3.4. Cycle CO₂ for hot start test (g) Cycle weighted CO₂ (g/kWh) (⁷):"

Annex 5, Appendix A.1, paragraph A.1.1.3., amend to read:

"A.1.1.3. Dry-to-wet concentration conversion

If the emissions are measured on a dry basis, the measured concentration c_d on dry basis shall be converted to the concentration c_w on a wet basis by means of equation (A.5-3). If water injection is used, Equations (A.5-4) and (A.5-7) are not applicable.:

$$c_{\rm w} = k_{\rm w} \cdot c_{\rm d} \tag{A.5-3}$$

where:

*k*_w = dry-to-wet conversion factor [-]

*c*_d = emission concentration on a dry basis [ppm] or [% vol]

For complete combustion, the dry-to-wet conversion factor for raw exhaust gas is written as $k_{w,a}$ [-] and shall be calculated by means of equation (A.5-4):

$$k_{\rm w,a} = \frac{\left(1.2442 \cdot H_{\rm a} + 111.19 \cdot w_{\rm H} \cdot \frac{q_{mf,i}}{q_{mad,i}}\right)}{\left(1 - \frac{1.2442 \cdot H_{\rm a} + 111.19 \cdot w_{\rm H} \cdot q_{mf,i}}{(q_{mad,i} \cdot k_{\rm f} \cdot 1000)}\right)}$$

$$k_{\rm w,a} = \frac{\left(1 - \frac{p_{\rm r}}{p_{\rm b}}\right)}{\left(1 - \frac{p_{\rm r}}{p_{\rm b}}\right)}$$
(A.5-4)

where:

*H*_a = intake air humidity [g H₂O/kg dry air]

 $q_{mf,i}$ = instantaneous fuel flow rate [kg/s]

 $q_{mad,i}$ = instantaneous dry intake air flow rate [kg/s]

*p*_r = water pressure after cooler [kPa]

 $p_{\rm b}$ = total barometric pressure [kPa]

*w*_H = hydrogen content of the fuel [% mass]

 $k_{\rm f}$ = combustion additional volume [m³/kg fuel]

with:

$$k_{\rm f} = 0.055594 \cdot w_{\rm H} + 0.0080021 \cdot w_{\rm N} + 0.0070046 \cdot w_{\rm O} \tag{A.5-5}$$

where:

*w*_H = hydrogen content of fuel [% mass]

 $w_{\rm N}$ = nitrogen content of fuel [% mass]

wo = oxygen content of fuel [% mass]

In equation (A.5-4), the ratio $p_{\rm r}/p_{\rm b}$ may be assumed:

$$\frac{1}{\left(1-\frac{p_{\rm r}}{p_{\rm b}}\right)} = 1.008 \tag{A.5-6}$$

For incomplete combustion (rich fuel air mixtures) and also for emission tests without direct air flow measurements, a second method of $k_{w,a}$ calculation is preferred:

$$k_{\rm w,a} = \frac{\frac{1}{1 + \alpha \cdot 0.005 \cdot (c_{\rm CO2} + c_{\rm CO})} - k_{\rm w1}}{1 - \frac{p_r}{p_b}}$$
(A.5-7)

where:

 c_{CO2} = concentration of CO₂ in the raw exhaust gas, on a dry basis [% vol]

*c*_{CO} = concentration of CO in the raw exhaust gas, on a dry basis [ppm]

*p*_r = water pressure after cooler [kPa]

*p*_b = total barometric pressure [kPa]

α = molar to carbon hydrogen ratio [-]

$$k_{\rm w1} = \frac{1.608 \cdot H_{\rm a}}{1000 + 1.608 \cdot H_{\rm a}}$$
(A.5-8)"

Annex 11, Title of Table A.11.1., amend to read:

"Table A.11.1.

Raw exhaust gas u and component densities (for emission concentration expressed in ppm) for engines operated solely on hydrogen"

II. Justification

1. Correct editorial errors and provide clarifications to the text of Supplement 1 to the 05 series of amendments to UN Regulation No. 96.