

Proposal for Supplement 1 to the 02 03 Series of Amendments to UN Regulation No. 66 (Strength of Superstructure (Buses))

Submitted by the expert from the Russian Federation *

The text reproduced below was prepared by the experts from the Russian Federation to amend UN Regulation No. 66 to add the definitions "escape hatch" and "emergency exit". The modifications to the existing text of the UN Regulation are marked in bold for new or strikethrough for deleted characters.

I. Proposal

Insert new paragraphs 2.34. and 2.35., to read:

"2.34. "Escape hatch" means an opening in the roof or the floor intended for use as an emergency exit by passengers in an emergency only.

2.35. "Emergency exit" means an emergency door, emergency window or escape hatch."

Insert new paragraphs 5.1.3. to 5.1.5., to read:

"5.1.3. The escape hatch in the roof is not jammed and remains operational. In the case of opening the escape hatch manually (in case the hatch is made of glass – without breaking it), the opening force applied in any direction shall not exceed 400 N;

***Note:* If there is only one escape hatch in the roof, the opening test shall be carried out from the outside. If there are two or more hatches, the opening test shall be carried out both from the inside and from the outside of the vehicle.**

5.1.4. There was no destruction of the seat attachments. During testing, deformation or damage of the seat-to-floor attachment components is acceptable, provided that the seat remains attached to the floor by the standard fasteners and cannot inadvertently move, shift, or rotate around the attachment points.

5.1.5. There was no movement of traumatic objects (fire extinguishers, glass breakers, etc.) in the residual space.

List of traumatic objects:

- 1. Luggage racks;**
- 2. Glass breaking tools;**
- 3. Refrigerator;**
- 4. A TV mounted;**
- 5. Fire extinguishers."**

Paragraph 5.4.5., amend to read:

"5.4.5 The basic principle is that the equivalent approval test method must be carried out in such a way that it represents the basic rollover test specified in Annex 5, and would allow assessing compliance with the requirements of paragraph 5.1 of this Regulation. If the equivalent approval test method chosen by the manufacturer cannot take account of some special feature or construction of the

* In accordance with the programme of work of the Inland Transport Committee for 2024 as outlined in proposed programme budget for 2024 (A/78/6 (Sect. 20), table 20.5), the World Forum will develop, harmonize and update UN Regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.



vehicle (e.g. air-conditioning installation on the roof, changing height of the waist rail, changing roof height) the complete vehicle may be required by the technical service to undergo the rollover test specified in Annex 5. **If the equivalent approval test method chosen by the manufacturer does not allow assessing compliance with the requirements of paragraph 5.1. of this Regulation, then the Contracting Party applying this Regulation may require the submission of the test results of the complete vehicle pursuant to Annex 5."**

Insert new paragraphs 10.12 to 10.16., to read:

- «10.12. As from the date of entry into force of the 03 series of amendments, no Contracting Parties applying this Regulation shall refuse to grant approval under this Regulation as amended by the 03 series of amendments.**
- 10.13. Until [24 months] after the date of entry into force of the 03 series of amendments, no Contracting Parties shall refuse national or regional approval of a vehicle approved to the preceding series of amendments to this Regulation.**
- 10.14. As from [01 October 2027], Contracting Parties may refuse first registration of a new vehicle which does not meet the requirements of the 03 series of amendments to this Regulation.**
- 10.15. Notwithstanding paragraphs 10.13 and 10.14, approvals of vehicle categories and classes granted to the preceding series of amendments to the Regulation, which are not affected by the 03 series of amendments, shall remain valid and Contracting Parties applying the Regulation shall continue to accept them.**
- 10.16. Contracting Parties applying this Regulation shall not refuse to grant extensions of approval to the preceding series of amendments to this Regulation.»**

Annex 5,

Paragraph 2.1., amend to read:

- "2.1. The vehicle to be tested need not be in a fully finished, "ready for operation" condition. ~~Generally~~ **Upon agreement with the technical service,** any alteration from the fully finished condition is acceptable if the basic features and behaviour of the superstructure are not influenced by it. **It is allowed to replace elements that do not affect the strength of the superstructure with the equivalent ones in mass and installation method, with the exception of the elements that can move and enter the residual space of passengers after the bus overturning.** The test vehicle shall be the same as its fully finished version in respect of the following:"

Paragraph 2.1.3., amend to read:

- "2.1.3. elements, which do not contribute to the strength of the superstructure and are too valuable to risk damage (e.g. drive chain, dashboard instrumentation, driver's seat, kitchen equipment, toilet equipment, etc.) can be replaced, **upon agreement with the technical service,** by additional elements equivalent in mass and method of installation. These additional elements must not have a reinforcing effect on the strength of superstructure."

Paragraph 2.1.5. to 2.1.5.2.3., amend to read:

- "2.1.5. In the case where occupant restraint devices are part of the vehicle type, a mass shall be attached to each seat fitted with an occupant restraint following ~~one of these two methods~~ **the method below,** at the choice of the manufacturer.

~~2.1.5.1. First method: That mass shall be:~~

~~2.1.5.1.1 50 per cent of the individual occupant mass (M_{mi}) of 68 kg,~~

~~2.1.5.1.2. placed to have its centre of gravity 100 mm above and 100 mm forward of the R point of the seat as defined in Regulation No. 21, Annex 5.2.1.~~

~~5.1.3. fixed rigidly and securely so that it does not break away during the test.~~

~~2.1.5.21. Second method: That mass~~ **That mass shall be:**

~~2.1.5.21.1. an anthropomorphic ballast with a mass of 68 kg and shall be restrained with a 2 point safety-belt. The ballast must allow guiding and positioning for safety-belts,~~

~~2.1.5.21.2. placed to have its centre of gravity and dimensioning according to figure A5.2.~~

~~2.1.5.21.3. fixed rigidly and securely so that it does not break away during the test."~~

Insert new paragraphs 2.2.4. and 2.2.5., to read:

"2.2.4. All escape hatches and emergency exits shall be closed.

2.2.5. Fire extinguishers shall be positioned in specially designated places and secured in a standard manner, as specified by the manufacturer. If it is possible to place different types of fire extinguishers in terms of size and mass, then, upon agreement with the technical service, a version of the fire extinguisher with the maximum parameters in terms of size and mass shall be provided for testing."

II. Justification

1. The definitions "escape hatch" and "emergency exit" are added, as these terms will be mentioned throughout the text of the Regulation. These definitions are consistent with those in UN Regulation No. 107.
2. Initially, it was proposed to include additional safety requirements in the test methods for complete buses according to annex 5, but at the working group meetings it was noted that such an approach entails non-equivalence of the test methods prescribed in this UN Regulation. The addition of the new provisions to section 5 would allow these requirements to be applied to all buses and at the same time confirm compliance with the requirements by all possible methods.
3. Paragraph 2.1.5. of annex 5 describes two options for the test masses: 34 and 68 kilograms. It is proposed to keep the only option with the mass of 68 kg, as this option is as close as possible to the real-world values and this allows full assessment of both the superstructure of the bus and the seat attachments.